



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2014010907689305

NAME AND ADDRESS OF THE APPLICANT

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME, MODEL AND SPECIFICATION

ITE POWER SUPPLY
See appendix (Altitude up to 5000m), Sale without cord sets

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022(Class A); GB 4943.1-2022; GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification (REFNO. CNCA-C09-01:2023).

Valid from: Jun.14, 2024

Valid until: Oct.24, 2027

Date of original issued: Apr.29, 2014

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2014010907689305

Appendix: Page 1 of 1

Model: GT*91120-***-T2*(The first "*" can be "M" or "-" or "H" for marketing purposes; The second "*" can be from "01" to "30", and the step is 1, which represents the rated output power; The third "*" to the "07.5", "10.5", "14.5", "19.5", "24", "36", "48"; The fourth "*" can be blank or "-0.1" to "-11.9" with a step of 0.01; The difference between the third "*" and the fourth "*" represents the output voltage, which ranges from 5-48VDC; Fifth six characters "*" represents any combination, can be "0-9" or "a-z" or "()" or "[]" or "-" or blank, on behalf of the market)

Input: 100-240V~, 50-60Hz, 1.5A

The list of series s is as follows:

Model	DC Output Voltage	Maximum Output Current	Maximum Output Power
GT*91120-*07.5*-T2*	5-7.5Vdc	4.0A	30W
GT*91120-*10.5*-T2*	7.6-10.5Vdc	3.94A	30W
GT*91120-*14.5*-T2*	10.6-14.5Vdc	2.83A	30W
GT*91120-*19.5*-T2*	14.6-19.5Vdc	2.0A	30W
GT*91120-*24*-T2*	19.6-24Vdc	1.6A	30W
GT*91120-*36*-T2*	24.1-36Vdc	1.25A	30W
GT*91120-*48*-T2*	36.1-48Vdc	0.83A	30W

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.