本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2014010907689314

NAME AND ADDRESS OF THE APPLICANT

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek,Inc.

186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd

Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME,MODEL AND SPECIFICATION

ITE POWER SUPPLY

See appendix (Altitude up to 5000m),Sale without cord set

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022（Class A）;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023).

Valid from: Jun.14,2024 **Valid until:** Nov.08,2027

Date of original issued: Apr.29,2014

The certificate information and validity could be checked by scanning the QR code below or logging in to the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

SIGNATURE: 谢肇煦

中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.

中国质量认证中心有限公司 11010610269466

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2014010907689314

Model：GT*91120-***-T3A*（1st “*” can be M or – or H, representing different market purposes; 2nd “*” can range from 01 to 30, stepped 1, representing the rated output power.3rd “*” can be "VV-X.X"; VV can be 07.5, 10.5, 14.5, 19.5, 24, 36, 48; 4th “*” can range from -0.1 to -11.9 or can be blank, stepped 0.01,3rd and 4th “*” together represents the output voltage of 5-48V, the step is 0.1V , representing the variable of output voltage, and the step is 0.1V. 5th “*” denote any six character = 0-9 or A-Z or () or [ ]or - or blank for marketing purposes.

Input：100-240V～，50-60Hz，1.5 A

Model list and output：see table

Model	DC output voltage	Maximum output current	Maximum output power
GT*91120-*07.5*-T3A*	5-7.5Vdc	4.0A	30W
GT*91120-*10.5*-T3A*	7.6-10.5Vdc	3.3A	30W
GT*91120-*14.5*-T3A*	10.6-14.5Vdc	2.83A	30W
GT*91120-*19.5*-T3A*	14.6-19.5Vdc	2.0A	30W
GT*91120-*24*-T3A*	19.6-24Vdc	1.6A	30W
GT*91120-*36*-T3A*	24.1-36Vdc	1.25A	30W
GT*91120-*48*-T3A*	36.1-48Vdc	0.83A	30W

This page is attached to the certificate and should be used at the same time as the certificate page.