



Ref. Certif. No.

SE-81694

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

ITE Power Supply

Name and address of the applicant
Nom et adresse du demandeur

GlobTek Inc.
186 Veterans Drive, Northvale NJ 07647,
UNITED STATES

Name and address of the manufacturer
Nom et adresse du fabricant

Same as above

Name and address of the factory
Nom et adresse de l'usine
Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème}

See page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

Input: GT*41134*****, GT*96060*****: 100-240V~, 50-60Hz,
0.3A or 0.6A; GT-41134-0606-W2-TAB: 120V~, 60Hz, 0.3A
Output: See page 2

Trademark (if any)
Marque de fabrique (si elle existe)



Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais
constructeur

-

Model / Type Ref.
Ref. De type

GT*41134*****, GT*96060*****, GT-41134-0606-W2-TAB

Additional information (if necessary may also be
reported on page 2)
Les informations complémentaires (si nécessaire,
peuvent être indiqués sur la 2^{ème} page)

See page 2

A sample of the product was tested and found
to be in conformity with
Un échantillon de ce produit a été essayé et a été
considéré conforme à la

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part
of this Certificate
Comme indiqué dans le Rapport d'essais numéro de
référence qui constitue partie de ce Certificat

151101267SHA-001

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Intertek

Signature:

Gary Hu

Date: 7 January 2016

**Factories
Les usines**

GlobTek Inc.
186 Veterans Drive, Northvale NJ 07647, UNITED STATES

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road, Suzhou Industrial Park,
Suzhou JiangSu, 215021, CHINA

**Additional information (if necessary)
Information complémentaire (si nécessaire)**

The national differences for US and CA have been checked.

Explanation for models GT*41134***** and GT*96060*****:

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" part can be "-" or "CC"; "-" = Constant Voltage Model, CC = Constant Current Model.

The 3rd "*" denotes the rated output wattage designation, which can be "01" to "06", with interval of 1.

The 4th "*" denotes the standard rated output voltage designation, which can be "03", "04", "06", "12", "15", "18", "24", "36" or "48". These standard rated output voltage designations correspond to seven isolated transformer models (See the appended table 4.1.2 for details). Each transformer model is identical in insulation construction including clearance and creepage except number of turns per coil.

The 5th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-11.9" with interval of 0.1, or blank to indicate no voltage different.

The 4th "*" and 5th "*" together denote the output voltage, with a range of 3.3 - 48 volts.

The 6th "*" = Blank means directly plug in model series,

= "-F" means Class I open frame model with connector which is fixing on the PCB,

= "-FW" means Class II open frame model with connector which is fixing on the PCB.

= "-FWT2" means open frame model with appliance inlet with Class II inlet C8 respectively,

= "-FT3A" means open frame model with appliance inlet with Class I inlet C6 respectively,

= "-FT3" means open frame model with appliance inlet with Class I inlet C14 respectively,

The last * denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Test performed on 3.3V, 5V, 9V and 48V output model as representative, and also performed on model GT-41134-0606-W2-TAB for reference. Test performed on 3.3V, 5V and 48V output model as representative for new added structure type.

Date: 7 January 2016

Signature: 

Additional information (if necessary)
Information complémentaire (si nécessaire)

Model	voltage	Max. current	Max. power
GT*41134**03*** GT*96060**03***	3.3V	1.8A	6W
GT*41134**04*** GT*96060**04***	3.4-4V	1.76A	6W
GT*41134**06*** GT*96060**06***	4.1-6V	1.46A	6W
GT*41134**12*** GT*96060**12***	6.1-12V	0.98A	6W
GT*41134**15*** GT*96060**15***	12.1-15V	0.50A	6W
GT*41134**18*** GT*96060**18***	15.1-18V	0.40A	6W
GT*41134**24*** GT*96060**24***	18.1-24V	0.33A	6W
GT*41134**36*** GT*96060**36***	24.1-36V	0.25A	6W
GT*41134**48*** GT*96060**48***	36.1-48V	0.16A	6W
GT-41134-0606-W2-TAB	6V	1A	6W

Date: 7 January 2016

Signature: 