



Ref. Certif. No.

**SE-92498**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR  
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

**CB TEST CERTIFICATE**

Product

LED driver

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


*Note: When more than one factory, please report on page 2*

See page 2

Ratings and principal characteristics

See page 2

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT\*961200P\*\*\*\*, GT\*96900P\*\*\*\*

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 61347-1:2015+A1  
IEC 61347-2-13:2014+A1

As shown in the Test Report Ref. No. which forms part of this Certificate

180501004SHA-001

This CB Test Certificate is issued by the National Certification Body

**Intertek Semko AB**  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

Date: 14 November 2018

**intertek**

Signature:

Hyden Li



**Factories**

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd  
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou,  
JiangSu, 215021, China

**Ratings and principal characteristics**

Input: 100-240V~, 50-60Hz, 1.5A,

Output: 12-54Vdc, Max. 9.2A, Max 120W

Model	Output Voltage	Max. output current	Max. output power	Rated maximum ambient temperature $t_a$
GT*96900P**- T2/T2A/T3/T3A/T3TAB/T W/TP/P2/P3/TP3/ TW3*	12-54Vdc	7.5A	90W	50°C
GT*961200P**- T2/T2A/T3/T3A/T3TAB/T W/TP/P2/P3/TP3/ TW3*	15-54Vdc	8A	120W	40°C
	12-14.9Vdc	9.2A	111W	40°C

**Additional information (if necessary)**

Explanation of type designation GT\*961200P\*\*\*\*, GT\*96900P\*\*\*\*:

The 1st "\*" part can be "M" or "-" or "H" for market identification and not related to safety.

The 2nd "\*" denotes the rated output wattage designation, which can be "-01" to "-120", "-" is optional, with interval of 1W.

The 3rd "\*" denotes the standard rated output voltage designation, which can be "12" to "54" or "12.0" to "54.0" with interval of 0.1V.

The 4th "\*" part

- T2 means desktop class II with C8 AC inlet
- T2A means desktop class II with C18 AC inlet
- T3 means desktop class I with C14 AC inlet
- T3TAB means desktop class I with C14 AC inlet and housing with a tab.
- T3A means desktop class I with C6 AC inlet
- TW means desktop class II with input wire without plug
- TP means desktop class II with power supply cord with plug
- TW3 means desktop class I with input wire without plug
- TP3 means desktop class I with power supply cord with plug
- P2 means Encapsulated type, class II, with two-core input wire, IP 68
- P3 means Encapsulated type, class I, with three-core input wire, IP 68

The last "\*" denotes any six character = 0-9 or A-Z or () or - or blank for marketing purposes

Date: 14 November 2018

Signature:

