



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2017010907015734

Valid from: Dec.18,2023

Valid until: Oct.24,2027

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co.,Ltd.
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m , Sale without cord set)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Oct.26,2017

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2017010907015734

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT*961200P****、GT*96900P**** (The 1st “*” part can be ‘M’ or ‘-’ or ‘H’. The 2nd “*” denotes the rated output wattage designation, which can be “-01” to “-120”, with interval of 1 and “-” can be omitted. The 3rd “*” denote the standard rated output voltage designation, which can be “12” to “54” or “12.0” to “54.0” in 0.1V increments. The 4th “*” can be -T2 or -T2A ,represent different AC inlet ;The last “*” denote any six character = 0-9 or A-Z or ()[] or – or blank. The 1st and 5th “*” for marketing purposes, no impact on Products safety and EMC characteristics)

Input : 100-240V ~ , 50-60Hz , 1.5A

Model	DC Output voltage (Vdc)	Max Output current(A)	Max Output power(W)
GT*96900P**-T2* GT*96900P**-T2A*	12-54Vdc	7.5A	90W
GT*961200P**-T2* GT*961200P**-T2A*	12-14.9Vdc	9.2A	111W
GT*961200P**-T2* GT*961200P**-T2A*	15-54Vdc	8A	120W



CHINA QUALITY CERTIFICATION CENTRE