

CERTIFICATE FOR EUROPEAN PRODUCT SAFETY

Reference No. SE-S-2001711

ITE Power supply

Type designation:

Certificate holder:

GlobTek, Inc. 186 Veterans Drive, Northvale, NJ 07647 USA

GT*961200P****, GT*96900P****, GT*41133-****

The product complies with the standard(s):

Date of expiry:

EU Directive information:

EN 62368-1:2014+A11

12 June, 2025

According to the principle of presumption of conformity, this certificate constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

Additional information in Appendix

Certification Body:

Signed:

tert	ek Semk	o AB, Product	Certification
	/		
		MI	
	C	Garv Hu	

Place: Kista - Stockholm

Date: 12 June, 2020

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX:

Reference No. SE-S-2001711

Technical Data:

Type designation Input Output

Trademark

Test Report Product information GT*961200P****, GT*96900P****, GT*41133-**** 100-240V~, 50-60Hz, 1.5A GT*41133-****: 12-48Vdc, Max. 7.5A, Max. 90W. GT*96900P***: 12-54Vdc, Max. 7.5A, Max. 90W. GT*961200P***: 12-54Vdc, Max. 9.2A, Max. 120W



191100311SHA-001

Explanation of model GT*41133-*****:

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "90", with interval of 1.

The 3rd "*" denotes the standard rated output voltage designation, which can be "16", "24", "35" and "48".

The 4th "*" part is optional, which can be "-0.1" to "-12.9" with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different. The 3rd "*" and 4th "*" together denote the output voltage, with a range of 12 - 48 volts

The 5th "*" can be:

-T2 means desktop class II with C8 AC inlet

-T3A means desktop class I or class II with functional earth with C6 AC inlet

-F means Open Frame class I or class II with functional earth -FW means Open Frame class II

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

Explanation of models GT*961200P**** and GT*96900P****: The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "-01" to "-120", with interval of 1 and "-" can be omitted.

The 3rd "*" denote the standard rated output voltage designation, which can be "12" to "54" or "12.0" to "54.0" in 0.1V increments

The 4th "*" can be:

-T2 means desktop class II with C8 AC inlet

-T2A means desktop class II with C18 AC inlet

-T3 means desktop class I or class II with functional earth with C14 AC inlet

-T3A means desktop class I or class II with functional earth with C6 AC inlet

-T3TAB means desktop class I or class II with functional earth with C14 AC inlet and housing with a tab.

-TW means desktop class II with input wire without plug

-TW3 means desktop class I or class II with functional earth with input wire without plug

-TP means desktop class II with power supply cord with plug

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.



APPENDIX:

Reference No. SE-S-2001711

-TP3 means desktop class I or class II with functional earth with power supply cord with plug

-P2 means Encapsulated Type, class II, with two-core input wire, IP68

-P3 means Encapsulated Type, class I or class II with functional earth, with three-core input wire, IP68

The last * denote any six character = 0-9 or A-Z or (), [] or – or blank for marketing purposes

Manufacturing Sites:

GlobTek (Suzhou) Co., Ltd. Building 4, No.76, JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu 215021, China

According to the principle of presumption of conformity, this certificate, which includes production control, constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

This presumption can expire before end of validity of this certificate due to new issued Standard or Amendment and changes within the EU legislation.

Certification Body:

Intertek Semko AB, Product Certification Place:

Date:

Place: Kista - Stockholm

12 June, 2020

Signed:

	/		
	/	1.)	
1	/	m	
della.	(Gary Hu	

This Certificate is for the exclusive use of Intertek's client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Certificate. Only the Client is authorized to permit copying or distribution of this Certificate and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek.