

CERTIFICATE

FOR EUROPEAN PRODUCT SAFETY

Reference No. SE-S-2100358

ICT/ITE POWER SUPPLY

Type designation: GT*96180_*****, GT*96300_*****, GT*91120_*****, GTM91128LI1CEL, GTM91128LI2CEL, GTM91128LI3CEL

Certificate holder: GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 United States of America

The product complies with the standard(s): EN 62368-1: 2014+A11

Date of expiry: 06 January, 2023

EU Directive information: According to the principle of presumption of conformity, this certificate constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

Additional information in Appendix

Certification Body: Intertek Semko AB, Product Certification **Place:** Shanghai

Signed:




Date: 12 March, 2021

Hyden Li

APPENDIX:

Reference No. SE-S-2100358

Technical Data:

Type designation	GT*96180-*****, GT*96300-*****, GT*91120-*****, GTM91128LI1CEL, GTM91128LI2CEL, GTM91128LI3CEL
Input	100-240V~, 50-60Hz or 50/60Hz, 0,6A / 1,0A / 1,5A;
Output	5-56VDC, Max. 4,5A, Max. 36W
Trademark	
Test Report	210201071SHA-001

Attachment:

Ratings and principal characteristics

When the 6th "*" is blank:

GT*96180-*****, Input: 100-240V~, 50-60Hz, 0.6A, Output: 5-48Vdc, Max. 3.6A, Max. 18W

GT*96300-*****, Input: 100-240V~, 50-60Hz, 1.0A, Output: 5-48Vdc, Max. 4.5A, Max. 36W

GT*91120-*****, Input: 100-240V~, 50-60Hz, 1.5A, Output: 5-48Vdc, Max. 4A, Max. 30W

When the 6th "*" = -AP or -PP or -SP:

GT*96180-*****, Input: 100-240V~, 50-60Hz, 0.6A, Output: 18-56Vdc, Max. 1.0A, Max. 18W

GT*96300-*****, Input: 100-240V~, 50-60Hz, 1.0A, Output: 18-56Vdc, Max. 2.0A, Max. 36W

GTM91128LI1CEL, Input: 100-240V~, 50-60Hz, 1.5A, Output: 4.2Vdc, 1.0A

GTM91128LI2CEL, Input: 100-240V~, 50-60Hz, 1.5A, Output: 8.4Vdc, 1.0A

GTM91128LI3CEL, Input: 100-240V~, 50-60Hz, 1.5A, Output: 12.6Vdc, 1.0A

Additional information (if necessary)

Explanation of model GT*96180-*****,

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "18", with interval of 1.

The 3rd "*" denotes the standard rated output voltage designation, which can be "07", "11", "17.9", "30", "38", "48", "54" or "56";

The 4th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-12.0" with interval of 0.01, or blank to indicate no voltage different.

The 3rd "*" and 4th "*" together denote the output voltage, with a range of 5 - 56 volts.

The 5th "*" = blank, it means wall plug in with interchangeable blade

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

The 6th "*" = Blank or -AP or -PP or -SP

-AP (with baby board) stands for Active POE (full IEEE compliant)

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

The last * denote any six character = 0-9 or A-Z or [] or - or blank for marketing purposes.

Explanation of model GT*96300-***** and GT*91120-*****

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "36", with interval of 1.

The 3rd "*" denotes the standard rated output voltage designation, which can be "07.5", "10.5", "14.5", "19.5", "24", "36", "48", "54" or "56";

The 4th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-11.9" with interval of 0.01, or blank to indicate no voltage different.

The 3rd "*" and 4th "*" together denote the output voltage, with a range of 5 - 56 volts.

APPENDIX:

Reference No. SE-S-2100358

The 5th "*" =-T2 means desktop class II with C8 AC inlet
=-T2A means desktop class II with C18 AC inlet
=-T3 means desktop class I or class II with functional earth with C14 AC inlet
=-T3A means desktop class I or class II with functional earth with C6 AC inlet
=-R2 means hybrid desktop housing class II with C8 AC inlet
=-R3A means hybrid desktop housing class I or class II with functional earth with C6 AC inlet
=-F means Open Frame class I or class II with functional earth
=-FW means Open Frame class II
=-P2 means Encapsulated class II
=-P3 means Encapsulated class I or class II with functional earth
The 6th "*" = Blank or -AP or -PP or -SP
-AP (with baby board) stands for Active POE (full IEEE compliant)
-PP (no baby board) stands for Passive POE
-SP (no baby board) stands for Simple POE
The last * denote any six character = 0-9 or A-Z or [] or - or blank for marketing purposes.
Group differences for CENELEC countries and national differences for Japan, Australia/New Zealand, US and Canadian are considered.

Manufacturing Sites: GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, JinLing East Road., Suzhou Industrial Park, Suzhou,
Jiangsu 215021, China

Safety related parts of the user instructions shall be written in a language acceptable to the country where the product is to be used.

The certificate applies for countries that have sanctioned the use of plugs/outlets according to subject standard sheet and component standard.

According to the principle of presumption of conformity, this certificate, which includes production control, constitutes support for an EC Declaration of Conformity and CE marking according to the Low Voltage Directive 2014/35/EU.

This presumption can expire before end of validity of this certificate due to new issued Standard or Amendment and changes within the EU legislation.

Certification Body: Intertek Semko AB, Product Certification **Place:** Shanghai

Signed:  **Date:** 12 March, 2021

Hyden Li