

# **VERIFICATION STATEMENT**

# EN 60950-1:2006+A11:2009+A1:2010+A12:2011+ A2:2013

## Information technology equipment – Safety – Part 1: General requirements

Report Reference No:	180401370SHA-002 (Based on CB certif. no. SE-91903)
Tested by (+ signature):	Albert Zhou Alberts Zhou
Approved by (+ signature)::	Will Wang
Date of issue:	2019-12-24
Contents:	3 pages
Testing laboratory Name:	Intertek Testing Services Shanghai
Address:	Building 86, 1198 Qinzhou Road (North), 200233 Shanghai, China
Testing location:	Same as above
Client Name:	GlobTek, Inc.
Address:	186 Veterans Dr. Northvale, NJ 07647 USA
Standard:	EN 60950-1:2006+A11:2009+A1:2010+A12:2011+A2:2013
Test procedure:	S mark
Non-standard test method:	N.A.
Test item Description:	ITE Power Supply
Trademark:	G <sup>GlobTek, Inc.</sup>
Model and/or type reference :	GT*961600P****, GT*961800P**** (The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety. The 2nd "*" can be "01" to "180", denotes the rated output wattage designation from 1W to 180W, with interval of 1W. The 3rd "*" can be "12" to "54" or "12.0" to "54.0", denote the standard rated output voltage designation from 12V to 54V, with interval of 0.1V The 4th "*" =-T2 means desktop class II with C8 AC inlet =-T2A means desktop class II with C18 AC inlet =-T3 means desktop class I with C14 AC inlet =-T3A means desktop class I with C6 AC inlet =-TW means desktop with input wires without plug =-TP means desktop with power cord and US plug The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.)

intertek				
Total Quality. Assured.				

Page 2 of 3

Rating(s):	Input: 100-240V~, 50-60Hz, 2.2A; Output: 12-54VDC, Max.13.33A, Max. 180W. Refer to page 2 for details.
Manufacture:	GlobTek, Inc.
	186 Veterans Dr. Northvale, NJ 07647 USA
Factory:	GlobTek (Suzhou) Co., Ltd
	Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China
Remarks for acceptance and review	w work conducted by above qualified testing laboratory
Sample Number reviewed::	1 pcs

Remark:	The product and the mentioned test reports comply with Swedish standard and nationals' deviations, if any. The sample as shown in following page(s) is still corresponding with the one mentioned in CB test report. We concluded this statement verifies that above standards are fulfilled.
Test item description:	No tests are needed for this product.
Statement for deviations, if any:	National difference for Sweden has been evaluated in CB report.

#### Model list:

Model	Input	Output voltage (Vdc)	Max. output current (A)	Max. output power (W)
GT*961600P**** GT*961800P****	100-240V~, 50-60Hz, 2.2A	12-14.9Vdc	13.33A	160W
GT*961600P**** GT*961800P****		15-18.9Vdc	11.33A	170W
GT*961600P**** GT*961800P****		19-54Vdc	9.47A	180W

## intertek Total Quality. Assured.

Page 3 of 3

Specification and key information involved in original CB certificate and test report   Involved Ref. Certif. no SE-91903   Issued date	
Issued date: 2018-09-17 Test item description: ITE Power Supply	
Test item description: ITE Power Supply	
Applicant's Name · GlobTek Inc	
Address 186 Veterans Dr. Northvale, NJ 07647 USA	
Manufacturer : GlobTek, Inc.	
186 Veterans Dr. Northvale, NJ 07647 USA	
Factory: GlobTek (Suzhou) Co., Ltd	
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suz JiangSu 215021, China	nou,
Technical data: Input: 100-240V~, 50-60Hz, 2.2A;	
Output: 12-54VDC, Max.13.33A, Max. 180W.	
Refer to page 2 for details.	
Referred standard : IEC 60950-1:2005 + A1:2009 + A2:2013 and EN 60950-1:2006 + A11:2009 + A1:2010 + A12:2011 + A2:2013 and National differen for CENELEC countries, Singapore, Japan, China, United Kingdo Australia/New Zealand, Korea, Canada and USA	
Model and/or type reference: GT*961600P****, GT*961800P****	
(The 1st "*" part can be 'M' or '-' or 'H' for market identification and related to safety. The 2nd "*" can be "01" to "180", denotes the rated output wattage designation from 1W to 180W, with interval of 1W. The 3rd "*" can be "12" to "54" or "12.0" to "54.0", denote the stand rated output voltage designation from 12V to 54V, with interval of The 4th "*" =-T2 means desktop class II with C8 AC inlet =-T2A means desktop class I with C18 AC inlet =-T3 means desktop class I with C14 AC inlet =-T3A means desktop class I with C6 AC inlet =-TW means desktop with input wires without plug =-TP means desktop with power cord and US plug The last * denote any six character = 0-9 or A-Z or ()[] or – or blan marketing purposes.)	lard 0.1V
Involved test report: 180401370SHA-001	