



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2025010907812668

NAME AND ADDRESS OF THE APPLICANT

GlobTek, Inc.
186 Veterans Dr Northvale, NJ 07647 , USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek, Inc.
186 Veterans Dr Northvale, NJ 07647 , USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME, MODEL AND SPECIFICATION

ICT/ITE Power supply
see appendix, (Altitude up to 5000m) (Sale without cord set)

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022 (Class A) ; GB 4943.1-2022; GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification (REFNO. CNCA-C09-01:2023).

Valid from: Sep.24,2025

Valid until: Sep.23,2030

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2025010907812668

Appendix: Page 1 of 1

Model: GTM96181-*PD***:

The 1st “*” denotes the rated output wattage designation, which can be “18” or “36”, with interval of 1.

The 2nd “*” = -PPS or blank, PPS means power supply with PPS (Programmable Power Supply) function, the rated output voltage can be “5.0” to “21.0” with interval of 0.1Vdc, the rated output maximum current can be 3.0A; blank means power supply without PPS (Programmable Power Supply) function, the rated output voltage can be “5.0” to “20.0” with interval of 0.1Vdc.

The 3th “*” = blank means wall plug in with interchangeable blade

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

The last *denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

The whole series output will be any one voltage/ current combinations (Power Profiles), between 5.0V and 21V.

Input: 100-240Vac, 50-60Hz, 1.2A

Model	Outout voltage (Vdc)	Maximum output current (A)	Maximum output power (W)
GTM96181-*PD-T2*	5.0-20.0	3.0	36W
GTM96181-*PD-T2A*	5.0-20.0	3.0	36W
GTM96181-*PD-PPS-T2*	5.0-21.0	3.0	36W
GTM96181-*PD-PPS-T2A*	5.0-21.0	3.0	36W

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.