

Registration No. : WTX25X11306821002
Reference No. : WTX25X11306821E002
Applicant : GlobTek, Inc.
Address : 186 Veterans Dr. Northvale, NJ 07647 USA
Manufacturer : GlobTek, Inc.
Address : 186 Veterans Dr. Northvale, NJ 07647 USA
Product Name : ICT/ITE Power Supply
Trade Name : 
Model(s) : See Model List
Ratings : Refer to the test report



Test Standards:

EN 60601-1-2:2015+A1:2021

EN 60601-1-2:2015+A1:2021: Medical electrical equipment – Part 1-2: General requirements for basic safety and essential performance – Collateral Standard: Electromagnetic disturbances – Requirements and tests



The statement is based on a single evaluation of the sample of above mentioned product(s). It does not imply an assessment of the whole production.

Waltek Testing Group (Shenzhen) Co., Ltd.

Tel: +86-755-33663308

Fax: +86-755-33663309

<http://www.waltek.com.cn>

E-mail: sem@waltek.com.cn

Ver 03.11.08.2025, WALTEK is registered trademark. Utilisation and application requires prior approval. Integral publication of this verification and adjoining report(s) is allowed.

ANNEX 1 TO ADDING MODEL

Certificate No. : WTX25X11306821002

Model List

GTM96183-*PD*-USB1C*:

The 1st "*" denotes the rated output wattage designation, which can be "18" or "36";

The 2nd "*" = "-PPS" or blank, "PPS" means power supply with PPS (programmable power supply) function, the rated output voltage can be "5.0" to "21.0" with interval of 0.1Vdc, the rated output maximum current can be 3.0A; blank means power supply without PPS (programmable power supply) function, the rated output voltage can be "5.0" to "20.0" with interval of 0.1Vdc;

The last "*" denote any six character=0-9 or A-Z or () or [] or – or blank for marketing purposes.

The whole series output will be any one voltage/current combinations (power profiles), between 5.0V and 21V.

GTM96181-*PD*:**

The 1st "*" denotes the rated output wattage designation, which can be "18" or "36"; with interval of 1.

The 2nd "*" = "-PPS" or blank, "PPS" means power supply with PPS (programmable power supply) function, the rated output voltage can be "5.0" to "21.0" with interval of 0.1Vdc, the rated output maximum current can be 3.0A; blank means power supply without PPS (programmable power supply) function, the rated output voltage can be "5.0" to "20.0" with interval of 0.1Vdc;

The 3rd "*" =blank means wall plug in with interchangeable blade,

= "-T2" means desktop class II with C8 AC inlet

= "-T2A" means desktop class II with C18 AC inlet

= "-T3" means desktop class I with C14 AC inlet

= "-T3A" means desktop class I with C6 AC inlet

The last "*" denote any six character=0-9 or A-Z or () or [] or – or blank for marketing purposes.

The whole series output will be any one voltage/current combinations (power profiles), between 5.0V and 21V.

Waltek Testing Group (Shenzhen) Co., Ltd.

Tel: +86-755-33663308

Fax: +86-755-33663309

<http://www.waltek.com.cn>E-mail: sem@waltek.com.cn

Ver 03.11.08.2025, WALTEK is registered trademark. Utilisation and application requires prior approval. Integral publication of this verification and adjoining report(s) is allowed.