



Ref. Certif. No.

SE-111232

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	ICT/ITE Power Supply
Name and address of the applicant	GlobTek, Inc. 186 Veterans Drive Northvale NJ 07647, USA
Name and address of the manufacturer	Same as applicant
Name and address of the factory	<input checked="" type="checkbox"/> Additional Information on page 2
Note: When more than one factory, please report on page 2	
Ratings and principal characteristics	See page 2
Trademark / Brand (if any)	
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	GTM46360-****, GTM96183-*PD*-USB1C*, GTM96181-*PD***
Additional information (if necessary may also be reported on page 2)	<input checked="" type="checkbox"/> Additional Information on page 2
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2018
As shown in the Test Report Ref. No. which forms part of this Certificate	220900735SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden
Date: 02 June, 2023

intertek

Signature:

Gary Hu



Ref. Certif. No.

SE-111232

Factories

1. GlobTek, Inc.
186 Veterans Drive Northvale NJ 07647, USA

2. GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz,
GTM46360-****: Max. 0.75A, Output: 3.0-5.0Vdc, Max. 6.0A, Max. 30W;
GTM96183-*PD*-USB1C*, GTM96181-*PD***: 1.2A, Output: 5.0-21.0Vdc, Max. 3.0A, Max. 36W

Additional information

Explanation of model GTM46360-****:

The 1st “**” denotes the rated output wattage designation, which can be “01” to “30”, with interval of 1.

The 2nd “**” denotes the standard rated output voltage designation, it can be “3.0” to “5.0” with interval of 0.1Vdc.

The 3th “**”=-USB1A means USB A*1

=-USB2A means USB A*2

=-USB1C means USB Type C*1

=-USB2C means USB Type C*2

=-USB1A1C means USB A*1 and USB Type C*1

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

Explanation of model GTM96183-*PD*-USB1C*:

The 1st “**” denotes the rated output wattage designation, which can be “18” or “36”.

The 2nd “**”= -PPS or blank, PPS means power supply with PPS (Programmable Power Supply) function, the rated output voltage can be “5.0” to “21.0” with interval of 0.1Vdc, the rated output maximum current can be 3.0A;blank means power supply without PPS (Programmable Power Supply) function, the rated output voltage can be “5.0” to “20.0” with interval of 0.1Vdc.

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

The whole series output will be any one voltage/current combinations (Power Profiles), between 5.0V and 21V.

Explanation of model GTM96181-*PD***:

The 1st “**” denotes the rated output wattage designation, which can be “18” or “36”, with interval of 1.

The 2nd “**”= -PPS or blank, PPS means power supply with PPS (Programmable Power Supply) function, the rated output voltage can be “5.0” to “21.0” with interval of 0.1Vdc, the rated output maximum current can be 3.0A;blank means power supply without PPS (Programmable Power Supply) function, the rated output voltage can be “5.0” to “20.0” with interval of 0.1Vdc.

The 3th “**”= blank means wall plug in with interchangeable blade

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

The last *denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

The whole series output will be any one voltage/ current combinations (Power Profiles), between 5.0V and 21V.

The group and national differences for the CENELEC countries, and the national differences for USA, Canada, Australia, New Zealand and Singapore have been checked.

Date: 02 June, 2023

Signature: 