

Certificate of Approval

Certificate No.: SAA-161679-EA

Certificate Holder: GlobTek, Inc

186 Veterans Drive, Northvale, NJ 07647

U.S.A.

Class Description: Power Supply or Charger

Product Description: ITE Power Supply

(Desktop type or Direct Plug-in)

Brand Name: G GLOBTEK, INC. (logo)
Model No.: GT**-**** Series

Markings: Input: 100-240V~ 50-60Hz 0.6A or 1.0A or 1.5A

Output: 5-56Vdc, 1-36W

Class II

Standard: AS/NZS 60950.1:2011 Inc A1

Conditions: Nil

Approval Mark: SAA-161679-EA or RCM

Date First Registered: 28 September 2016
Date of Expiry: 28 September 2021

For and on Behalf of SAA Approvals Pty Ltd

SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to: www.saaapprovals.com.au





Issued: 28-09-16 161679/1



Certificate of Approval

Addendum

Certificate No.: SAA-161679-EA

Date of Issue: 28 September 2016

Class Description: Power Supply or Charger

Product Description: ITE Power Supply (Desktop type or Direct Plug-in)

General Modification:

1st '*' can be 'M', '-' or 'H' and is for marketing purposes only;

2nd '*' denotes market identification and can be '96180', '96300', '91120' or '91128';

3rd '*' denotes rated output wattage designation (W) and can be '01-36' in steps of 1W;

4th '*' denotes standard rated output voltage designation:

When 2^{nd} '*' = '96180', 4th '*' can be '07', '11', '17.9', '30', '38', '48', '54' or '56';

When 2^{nd} (*' = '96300' or '91120', 4th '*' can be '07.5', '10.5', '14.5', '19.5', '24', '36', '48', '54' or '56';

5th '*' denotes optional deviation, subtracted from standard output voltage, which can be '-0.01 to -12.0' in steps of 0.01, or blank to indicate no voltage difference

(Note: the 4th & 5th '*' together denote the output voltage with a range of 5-56V);

6th '*' denotes type and can be:

blank for plug-in type with interchangeable plug;

'-T2' for desktop, Class II, with C8 AC inlet,

'-T2A' for desktop, Class II, with C18 AC inlet,

'-T3' for desktop, Class I, with C14 AC inlet, or

'-T3A' for desktop, Class I, with C6 AC inlet;

7th '*' denotes POE function and can be:

'-AP' (with baby board) Active POE (IEEE compliant),

'-PP' (no baby board) Passive POE or

'-SP' (no baby board) Simple POE;

(Note: When 2^{nd} * '*' = '91128', the model will be 'GTM91128L11CEL' (Output: 4.2V, 1000mA),


'GTM91128LI2CEL' (Output: 8.4, 1000mA) or 'GTM91128LI3CEL' (Output: 12.6V, 1000mA); and

8th '*' can be a combination of any six characters of the following: '0-9', 'A-Z', '(', ')', '[', ']', '-' or blank and is for marketing purposes only.

For and on Behalf of SAA Approvals Pty Ltd

SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.







Issued: 28-09-16 161679/2