



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO.: 2016010907908062

NAME AND ADDRESS OF THE APPLICANT

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND ADDRESS OF THE MANUFACTURER

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND LOCATION OF THE FACTORY

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT NAME, MODEL AND SPECIFICATION

ITE POWER SUPPLY

See appendix (Altitude up to 5000m) (Sale without cord set)

STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB 17625.1-2022 (Class A); GB 4943.1-2022; GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of
implementation rules for compulsory certification (REFNO. CNCA-C09-01:2023).

Valid from: Apr.30,2024

Valid until: Aug.12,2026

Date of original issued: Oct.09,2016

The certificate information and validity could be checked by scanning the QR code below or logging in to
the website of the issuing authority, or on the website of the CNCA (www.cnca.gov.cn).

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P



SIGNATURE:

谢肇煦



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

本翻译文件不具有法律效力，
不得单独使用
This translated document
does not have legal validity and
cannot be used in isolation

CERTIFICATE NO. : 2016010907908062

Appendix: Page 1 of 1

GT*96300-*****

(The 1st "*" part can be 'M' or '-' or 'H' for market identification.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "36" with interval of 1.

The 3rd "*" denotes the standard rated output voltage designation, which can be "07.5", "10.5", "14.5", "19.5", "36", "48".

The 4th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-11.9" interval of 0.1, or blank to indicate no voltage different. The 3rd "*" and 4th "*" together denote the output voltage, with a range of 5 - 48 volts.

The 5th "*" can be -T2 or -T2A or -R2, represents for different constructions.

The 6th "*" denote any six character = 0-9 or A-Z or () or [] or - or blank for marketing purposes.)

Input: 100-240V~, 50-60Hz, 1.0A

Model	DC Output Voltage	Max Output Current	Max Output Power
GT*96300-*07.5***	5-7.5Vdc	4.5A	22.5W
GT*96300-*10.5***	7.6-9Vdc	3.94A	30W
GT*96300-*10.5***	9.1-10.5Vdc	3.95A	36W
GT*96300-*14.5***	10.6-14.5Vdc	3.39A	36W
GT*96300-*19.5***	14.6-19.5Vdc	2.46A	36W
GT*96300-*24***	19.6-24Vdc	1.83A	36W
GT*96300-*36***	24.1-36Vdc	1.49A	36W
GT*96300-*48***	36.1-48Vdc	0.99A	36W

This page is attached to the certificate and should be used at the same time as the certificate page.



中国质量认证中心
CHINA QUALITY CERTIFICATION CENTRE

CHINA QUALITY CERTIFICATION CENTRE CO., LTD.