



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2017010907972821

Valid from: Nov.08,2023

Valid until: Apr.11,2027

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m) (Sale without cord set)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jun.08,2017

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2017010907972821

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT*96600-**-** (1st * can be "M", "-" 或 "H", for market identification ; 2nd * denotes the rated output wattage designation, which can be "01" to "65", with interval of 1 ; 3rd * denote the standard rated output voltage designation, which can be "05" to "54" or "5.0" to "54.0" in 0.1V increments. ; 4th * can be T2 or R2 or T2A , Represents different appearance structures ; fifth * denote any six character = 0-9 or A-Z or [] or - or blank for marketing purposes; The first, fourth and fifth * do not affect product safety and EMC performance)

Input : 100-240V ~ , 50-60Hz , 1.5A

The specifications are as follows

Model	DC Output voltage (Vdc)	Max Output current (A)	Max Output power (W)
GT*96600-**-**	5-6.7V	8	40
	6.8-11	6	60
	11.1-54	5.42	65



CHINA QUALITY CERTIFICATION CENTRE