

Handled by
Candy Liang
Direct telephone
+86 21 61278415
Reference
1809804
E-mail
Shanghai-LC@intertek.com
Your Reference
180200874SHA

Intertek S Mark Certificate with No. 1809804

We are pleased to enclose the Intertek S Mark Certificate you have applied for.

Thank You for S Marking your Products!

You have taken the first step to S Mark, but have you taken the next step by letting your customers know about your investment? When you use the S Mark in your marketing you are making clear that your company is truly committed to quality and safety. Positioning and differentiate yourself as a company which is dedicated to safety enables you to increase your sales – because in Europe safety sells.

The S Mark is highly recognized among retailers and authorities since 1926.

The S Mark also strengthens your brand by signaling that safety is important to your company and that you care about the safety of your clients. Since we value you as a customer we want to make sure you are getting the best value out of the S Mark. Many of our customers are already using the S Mark in their marketing. Popular media to use the mark is in campaigns, on packaging and in product catalogues. To find out more and to download tools, please visit <http://www.intertek.com/marks/s/>.



If you have any questions don't hesitate to contact us at info-sweden@intertek.com

Additional part of the certification

In addition to your product certification, we are conducting inspections at your manufacturing site/s. The inspections are carried out by our inspectors or subcontractors. For details of the technical requirements for these inspections, please visit <http://intertek.com/europeaninspection>

Your success is important to us!

Best Regards,

A blue ink signature, appearing to be 'Gary Hu', is written over a white background.

Gary Hu
Local Certification Manager

Certificate



for European Product Safety

Reference No. 1809804

Medical Power supply

Type designation GT*91099-***-**, GT*96600-***-**, GT*96600-*56***

Certificate holder **GlobTek, Inc.**
186 Veterans Drive Northvale NJ 07647
USA

The product complies with the standard(s) EN 60601-1: 2006+ A1: 2013+A12: 2014
EN 60601-1-11: 2015

Date of expiry 14 May 2023

Additional information in Appendix.

Certification Body Intertek Semko AB, Product Certification

Place Shanghai

Signed

Gary Hu

Date 14 May 2018

Page 1 of 4

This certificate is issued in accordance with the terms and conditions set out in the Appendix.



Intertek Appendix

Reference No. 1809804

Technical data

Type designation

GT*91099-***-**, GT*96600-***-**, GT*96600-*56***

Input

GT*91099-***-**: 1.5A, 100-240V~, 50-60Hz;
GT*96600-***-**: 1.5A, 100-240V~, 50-60Hz;
GT*96600-*56***: 2.0A, 100-240V~, 50-60Hz

Output

GT*91099-***-**: 5-48V, Max. 60W;
GT*96600-***-**: 5-54V, Max. 65W;
GT*96600-*56***: 56VDC, Max. 70W.
Alternate Rating:
For models GTM96600-2005-R2 / GTM96600-2005-R3A:
output 5VDC, 4.0A at Tma=70 Deg.C;
For models GTM96600-2412-R2 / GTM96600-2412-R3A:
output 12VDC, 2.0A at Tma=70 Deg.C;
For models GTM96600-2436-R2 / GTM96600-2436-R3A:
output 36VDC, 0.66A at Tma=70 Deg.C;
For models GTM96600-2448-R2 / GTM96600-2448-R3A:
output 48VDC, 0.5A at Tma=70 Deg.C;
For models GTM96600-2454-R2 / GTM96600-2454-R3A:
output 54VDC, 0.44A at Tma=70 Deg.C;
For models GT-96600-7056-T3-AP/ GT-96600-7056-T2-AP:
output 56VDC, 1.25A at Tma=40 Deg.C

BRAND name:

GlobTek

Product information

Details see attachment

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.



Intertek Appendix

Reference No. 1809804

Attachment:

GT*91099-***-** and GT*96600-***-** series

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "65", with interval of 1.

When model= GT*91099-***-**,

The 3rd "*" denotes the standard rated output voltage designation, which can be "09", "15", "24", "48";

The 4th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-23.9" with interval of 0.01, or blank to indicate no voltage different.

The 3rd "*" and 4th "*" together denote the output voltage, with a range of 5–48 volts.

When model=GT*96600-***-**,

The 3rd "*" denote the standard rated output voltage designation, which can be "05" to "54" or "5.0" to "54.0" in 0.1V increments.

The 4th "*" = Blank

The 5th "*" = T2 means desktop class II with C8 AC inlet

=T2A means desktop class II with C18 AC inlet

=T3 means desktop class I with C14 AC inlet

=T3A means desktop class I with C6 AC inlet

=T2L means desktop class II with C8 AC inlet and housing with a DC jack

=T2AL means desktop class II with C18 AC inlet and housing with a DC jack

=T3L means desktop class I with C14 AC inlet and housing with a DC jack

=T3AL means desktop class I with C6 AC inlet and housing with a DC jack

=R2 means hybrid desktop housing class II with C8 AC inlet

=R3A means hybrid desktop housing class I with C6 AC inlet

=F means Open Frame class I

=FW means Open Frame class II

=P2 means Encapsulated class II

=P3 means Encapsulated class I

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

For details please refer to model list table.

GT*96600-*56***

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "70", with interval of 1.

The 3rd "*" = -T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

The 4th "*" = -AP means standing for Active POE with baby board.

= -PP means standing for Passive POE without baby board

= -SP means standing for Simple POE without baby board

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.




Reference No. 1809804

Manufacturing site(s) GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou,
JiangSu 215121,
P.R. China

Safety related parts of the user instructions shall be written in a language acceptable to the country where the product is to be used.

If the product is to be marketed in different European countries, it must be provided with a certified plug appropriate for each country.

<i>Certification Body</i>	Intertek Semko AB, Product Certification	<i>Place</i>	Shanghai
<i>Signed</i>	 _____ Gary Hu	<i>Date</i>	14 May 2018

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.