



Ref. Certif. No.

SE-93988

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

GlobTek Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.5A,
Output: 3.6-20VDC, Max. 4.6A, Max. 60W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*96605-G2*****

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part of this Certificate

180500334SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 3 May 2019

intertek

Signature:

Gary Hu

Factories

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road, Suzhou Industrial Park, Suzhou JiangSu, 215021, China

GlobTek Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

Additional information

Group differences for CENELEC countries and national differences for Singapore, Japan, China, Australia/New Zealand, Korea, United Kingdom, USA and Canada are considered.

Explanation of model GT*96605-G2*****

The 1st symbol "*" can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd symbol "*" can be A1, A2, A3 denote different DC output voltage

When 2nd *=A1: 5V/4.6A, 5.8V/4.6A, 9V/4.4A, 12V/4A, 15V/3.6A and 20V/3A

When 2nd *=A2: 5V/3A, 5.8V/3A, 9V/3A, 12V/3A, 15V/3A and 20V/3A

When 2nd *=A3: 5V/4.6A, 5.8V/4.6A, 9V/4.4A, 12V/4A, 15V/3.6A, 20V/3A and any one voltage/current combinations (Power Profiles), between 3.6V and 20V.

The 3rd symbol "*" denotes blank or the rated output wattage designation, which can be "01" to "60", with interval of 0.1W.

The 4th symbol "*" =-T2 means desktop class II with C8 AC inlet.

=-T2A means desktop class II with C18 AC inlet.

=-T3 means desktop class I with C14 AC inlet.

=-T3A means desktop class I with C6 AC inlet.

=-T3F means desktop class I with C14 AC inlet with FLOATING OUTPUT.

=-T3AF means desktop class I with C6 AC inlet with FLOATING OUTPUT.

=-R2 means hybrid desktop housing class II with C8 AC inlet.

=-R3A means hybrid desktop housing class I with C6 AC inlet.

=-R3AF means hybrid desktop housing class I with C6 AC inlet with FLOATING OUTPUT.

The 5th symbol "*" can be blank or -RA. -RA denotes the Product with RIGHT ANGLE daughter board (no output cord), blank denotes the product with output cord.

The last symbol "*" denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Model List:

Model	Input	Output voltage (Vdc)	Max. output current (A)	Max. output power (W)
GT*96605-G2A1- T2/T2A/T3/T3A/T3F/T3AF/ R2/R3A/R3AF**	100-240VAC, 50-60Hz, 1.5A	5V/4.6A, 5.8V/4.6A, 9V/4.4A, 12V/4A, 15V/3.6A and 20V/3A		
GT*96605-G2A2- T2/T2A/T3/T3A/T3F/T3AF/ R2/R3A/R3AF**		5V/3A, 5.8V/3A, 9V/3A, 12V/3A, 15V/3A and 20V/3A		
GT*96605-G2A3*- T2/T2A/T3/T3A/T3F/T3AF/ R2/R3A/R3AF**		3.6V - 6.9V	4.6A	30.8W
		7.0V - 11.9V	4.4A	48.0W
		12.0V - 14.9V	4.0A	54.0W
	15.0V - 17.9V	3.6A	57.6W	
		18.0V - 20.0V	3.2A	60.0W

Date: 3 May 2019

Signature: 