

Ref. Certif. No.
SE-105308

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Name and address of the applicant

Name and address of the manufacturer

Name and address of the factory
Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Trademark (if any)

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

Additional information (if necessary may also be reported on page 2)

A sample of the product was tested and found to be in conformity with

As shown in the Test Report Ref. No. which forms part of this Certificate


ICT/ITE Power Supply

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 United States of America

Same as applicant

see page 2

Input: 100-240V~, 50-60Hz or 50/60Hz, 1.5A;
Output: 3.6-20VDC, Max. 4.6A, Max. 60W



-

GT*96605-G2*****

See page 2

IEC 62368-1:2014

200300450SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden



Signature:

Date: 28 June, 2021

Hyden Li

Factories

GlobTek (Suzhou) Co., Ltd.
 Building 4, No.76, JinLing East Road, Suzhou Industrial Park,
 Suzhou, Jiangsu 215021, China

GlobTek, Inc.
 186 Veterans Dr. Northvale, NJ 07647 United States of America

Additional information

Group differences for CENELEC countries and national differences for Japan, Australia/New Zealand, US and Canadian are considered.

Explanation of type designation GT*96605-G2****:

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" can be A1, A2, A3 or any words for market use.

The 3rd "*" denotes blank or the rated output wattage designation, which can be "01" to "60", with interval of 0.1W.

The 4th "*" =-T2 means desktop class II with C8 AC inlet.

=-T2A means desktop class II with C18 AC inlet.

=-T3 means desktop class I or class II with functional earth with C14 AC inlet.

=-T3A means desktop class I or class II with functional earth with C6 AC inlet.

=-T3F means desktop class I or class II with functional earth with C14 AC inlet with FLOATING OUTPUT.

=-T3AF means desktop class I or class II with functional earth with C6 AC inlet with FLOATING OUTPUT.

=-R2 means hybrid desktop housing class II with C8 AC inlet.

=-R3A means hybrid desktop housing class I or class II with functional earth with C6 AC inlet.

=-R3AF means hybrid desktop housing class I or class II with functional earth with C6 AC inlet with FLOATING OUTPUT.

The 5th "*" can be blank or -RA. -RA denotes the Product with RIGHT ANGLE daughter board (no output cord); blank denotes the product with output cord.

The last * denote any six character = 0-9 or A-Z or () [] or - or blank for marketing purposes.

The whole series output will be any one voltage/current combinations (Power Profiles), between 3.6V and 20V.

Model list:

Model	Input	Output voltage (Vdc)	Max. output current (A)	Max. output power (W)
GT*96605-G2**- T2/T2A/T3/T3A/T3F/T3AF/ R2/R3A/R3AF**	100-240VAC, 50-60Hz or 50/60Hz, 1.5A	3.6V - 6.9V	4.6A	30.8W
		7.0V - 11.9V	4.4A	48.0W
		12.0V - 14.9V	4.0A	54.0W
		15.0V - 17.9V	3.6A	57.6W
		18.0V - 20.0V	3.2A	60.0W

Date: 28 June, 2021

Signature:

