



Ref. Certif. No.

SE-86669

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR  
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Power supply (Limited use for House Hold products only)

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as above

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.5A  
GT\*96900P\*\*\*\* Output: 12-36Vdc, Max. 7.5A, Max. 90W  
GT\*961200P\*\*\*\* Output: 12-36Vdc, Max. 9.2A, Max. 120W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT\*96900P\*\*\*\*, GT\*961200P\*\*\*\*

Additional information (if necessary may also be  
reported on page 2)

See page 2

A sample of the product was tested and found  
to be in conformity with

IEC 60335-1:2010+A1

As shown in the Test Report Ref. No. which forms part  
of this Certificate

161200822SHA-002

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

Date: 19 April 2017

Intertek

Signature:

  
Gary Hu

**Factories**

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd  
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

**Additional information (if necessary)**

Explanation of model designations GT\*96900P\*\*\*\*, GT\*961200P\*\*\*\*:

The 1st "\*" part can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd "\*" denotes the rated output wattage designation, which can be "-01" to "-120", with interval of 1 and "-" can be omitted.

The 3rd "\*" denote the standard rated output voltage designation, which can be "12" to "36" or "12.0" to "36.0" in 0.1V increments

The 4th "\*" :

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3TAB means desktop class I with C14 AC inlet and housing with a tab.

=-T3A means desktop class I with C6 AC inlet

The last \* denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes

Date: 19 April 2017

Signature: 