

Certificate of Approval

Certificate No.: SAA-170646-EA

Certificate Holder: GlobTek, Inc

> 186 Veterans Drive, Northvale, NJ 07647

U.S.A.

Class Description: Power Supply or Charger

Product Description: ITE Power Supply (Desktop type)

> **Brand Name:** G GLOBTEK. INC.

Model No.: GT*961200P**** Series Markings:

Input: 100-240V~ 50-60Hz 1.5A Output: 12-54Vdc, Max 120W

Class II

AS/NZS 60950.1:2015 Standard:

Conditions: Nil

Approval Mark: SAA-170646-EA or RCM

Date First Registered: 24 July 2017 Date of Expiry: 24 July 2022

For and on Behalf of SAA Approvals Pty Ltd

SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to: www.saaapprovals.com.au





www.jas-anz.org/register



Issued: 24-07-17 170646/1



Certificate of Approval

Addendum

Certificate No.: SAA-170646-EA

Date of Issue: 24 July 2017

Class Description: Power Supply or Charger

Product Description: ITE Power Supply (Desktop type)

General Modification:

For GT*961200P**** Series:

1st '*' denotes market identification only and can be 'M', '-' or 'H';

Description

2nd '*' denotes output wattage and can be '-01' to '-120' in increments of 1W where '-' can be blank;

3rd '*' denotes output voltage and can be '12-54' or '12.0-54.0' in increments of 0.1Vdc;

4th '*' denotes class and inlet type and can be 'T2' for desktop class II with C8 AC inlet,

'T2A' for desktop class II with C18 AC inlet, 'T3' for desktop class I with C14 AC inlet,

'T3TAB' for desktop class I with C14 AC inlet and housing with a tab or

'T3A for desktop class I with C6 AC inlet; and

5th '*' is for marketing purposes only and can be '0-9', 'A-Z', '(', ')', '[', ']', '-' or blank.

Additional Models

0000**** C--!-- C!--!!--

GT*96900P**** Series

Similar to GT*961200P**** Series except for model number.

GT*41133-**** Series

Similar to GT*961200P**** Series except rated output 16-48Vdc, Max 90W and where:

2nd '*' denotes output wattage and can be '01' to '90' in increments of 1W;

3rd '*' denotes output voltage and can be '16', '24', '35' or '48';

4th '*' denotes voltage deviation and can be '-0.1' to '-12.9' in increments of 0.1Vdc or can be blank;

5th '*' denotes class and inlet type and can be 'T2' for desktop class II with C8 AC inlet,

'T3A for desktop class I with C6 AC inlet, 'F' for open frame class I or

'FW' for open frame Class II; and

6th '*' is for marketing purposes only and can be '0-9', 'A-Z', '(', ')', '[', ']', '-' or blank.

Note: 3rd and 4th '*' together denote output voltage with a range of 12-48Vdc.

For and on Behalf of SAA Approvals Pty Ltd

SAA Approvals Pty Ltd as accredited by JAS-ANZ under ISO/IEC 17065 certifies in accordance with the SAA Approvals Electrical Product Safety Certification Scheme that the product nominated in this certificate complies with standard/s listed.

When using the RCM the requirements of all relevant parts of AS/NZS 4417 applicable to the article must be fulfilled.

For SAA Contact Details and to verify this Certificate go to: www.saaapprovals.com.au





Issued: 24-07-17 170646/2