CERTIFICATE OF COMPLIANCE

Certificate Number 20151012-E170507

Report Reference E170507-20130923

Issue Date 2015-OCTOBER-12

Issued to: GLOBTEK INC

186 VETERANS DR

NORTHVALE, NJ 07647

United States

This is to certify that representative samples of

POWER SUPPLIES, INFORMATION TECHNOLOGY EQUIPMENT INCLUDING ELECTRICAL BUSINESS

EQUIPMENT

For models refer to Addendum Page

Have been investigated by UL in accordance with the

Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60950-1 and CSA C22.2 No. 60950-1-03 (Information

Technology Equipment - Safety - Part 1: General

Requirements)

Additional Information: See the UL Online Certifications Directory at

www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/



CERTIFICATE OF COMPLIANCE

Certificate Number 20151012-E170507

Report Reference E170507-20130923

Issue Date 2015-OCTOBER-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Switching Power Supplies - GT-21089-0903-A.B-CD, GT-21089-1305-A.B-CD, GT-21089-1506-A.B-CD, GT-21089-1509-A.B-CD, GT-21089-1512-A.B-CD, GT-21089-1815-A.B-CD, GT-21089-1818-A.B-CD, GT-21089-1824-A.B-CD.

Switch-mode Power Supply - GT-B1057 Series, GT-9100P Series

Switching Adapter - GT-81081-60x-y-a Series, GT-51084-12N12.

Direct Plug-in Switch-mode Power Supply - GT-41060 (- or CC) WWVV-X.X Family (#), (#) where 41060: Series Code; (- or CC): "-" = Constant Voltage Model, CC = Constant Current Model; WW: Rated Wattage; VV: Rated Voltage; X.X-Denotes Voltage Differentiator; Subtract X.X from rated voltage.

Power Unit - GT-2S5024D-R-ES, GT-2S5024D-R-ES+

Direct Plug In Switching Adapter - GT-81082-0506.5-X.X-USB-W2 (#),(#) where X.X is optional for specifying the output voltage deviations in 0.1 increments, and X.X is to be subtracted from the base rated voltage of 6.5.

Direct Plug In Switching Adapter - GT-81083-0404-X.X-W2 (\$), GT-81083-0506-X.X-W2 (\$), GT-81083-0509-X.X-W2 (\$), GT-81083-0513-X.X-W2 (\$), GT-81083-0404-AUS-X.X-W2 (\$), GT-81083-0506-AUS-X.X-W2 (\$), GT-81083-0509-AUS-X.X-W2 (\$), GT-81083-0513-AUS-X.X-W2 (\$), where X.X is optional for specifying the output voltage deviations in 0.1 increments, and X.X is to be subtracted from the base rated voltage.

Switching Power Adapter - GTM91120-WWVV-X.X-TB series (&),(&) M can be "M" or "-" for market identification and not related to safety, WW is the rated output wattage designation, with a maximum value of "30"; VV is the standard rated output voltage designation, with a maximum value of "48"; -X.X denotes the optional deviation, subtracted or added from standard output voltage in 0.1 volt increments or blank to indicate the no voltage different; B can be 2 or 3A, 2 means Class II, 3A means class I

Bamble Director North A

Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/



CERTIFICATE OF COMPLIANCE

Certificate Number 20151012-E170507

Report Reference E170507-20130923

Issue Date 2015-OCTOBER-12

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Switching Power Adapter - GTM91099-WWVV-X.X-AB series (#),(#) M can be "M" or "-" for market identification and not related to safety; WW is the rated output wattage designation, with a maximum value of "60"; VV is the standard rated output voltage designation, with a maximum value of "48"; -X.X denotes the optional deviation, subtracted or added from standard output voltage in 0.1 volt increments or blank to indicate the no voltage different; VV-X.X together denotes the voltage range 5V to 48V; A:T is External/Desktop model; B can be 2 or 3A, 2 presents Class II, 3A presents Class I.

ITE POWER SUPPLY - GT-93020-0324



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at http://ul.com/aboutul/locations/

