

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ICT/ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647, New Jersey,
USA

Name and address of the manufacturer

GlobTek, Inc.
186 Veterans Drive, Northvale NJ 07647, New Jersey,
USA

Name and address of the factory

See next page

Note: When more than one factory, please report on page 2 Additional Information on page 2

Ratings and principal characteristics

Input: 100-240 Vac.; 0,3 A; 50-60 Hz
Output: 3-24 Vdc; max. 6 W (see next page for details)

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

/

Model / Type Ref.

GT-41076-WWVV-X.X series
(see next page for details)

Additional information (if necessary may also be reported on page 2)

Unit also complies with EN IEC 62368-1:2020 +
A11:2020

A sample of the product was tested and found to be in conformity with

 Additional Information on page 2
IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

T223-0246/23 (2023-05-12)

This CB Test Certificate is issued by the National Certification Body

SIQ Ljubljana, Mašera-Spasičeva ulica 10, SI-1000 Ljubljana, Slovenia
T +386 1 4778 100, F +386 1 4778 444, info@siq.si, www.siq.si

SIQ Ljubljana is accredited by Slovenian Accreditation with accreditation number CP-001 in the field of certification of products, processes and services (SIST EN ISO/IEC 17065).

Date: 2023-05-12

Signature: Bojan Pečavar

Name and address of the factory:

1) GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, New Jersey, USA

2) GlobTek (Suzhou) Co. Ltd.
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou JiangSu, 215021, China

Ratings and principal characteristics:

GT-41076-WWVV-X.X series

WW is the standard output wattage, with a maximum value of "06",

VV is the standard rated output voltage designation, with a maximum value of "24", which can be 03, 05, 09, 12, 15, 18, 20, 24.

-X.X is optional, which can be "-0.1" to "-3.9", denote the output voltage differentiator, subtracting -X.X volts from standard output voltage VV in 0.1V increments, the actual output voltage range is 3-24Vdc, blank is to indicate the no voltage different.

Model	Output Voltage(V)	Max. output current (A)	Max. output wattage (W)
GT-41076-0603	3	2	6
GT-41076-WW05-X.X	3.1-5.0	1,93	6
GT-41076-WW09-X.X	5.1-9.0	1,17	6
GT-41076-WW12-X.X	9.1-12.0	0,65	6
GT-41076-WW15-X.X	12.1-15.0	0,49	6
GT-41076-WW18-X.X	15.1-18.0	0,39	6
GT-41076-WW20-X.X	18.1-20.0	0,33	6
GT-41076-WW24-X.X	20.1-24.0	0,29	6

Additional information (if necessary)

Date: 2023-05-12

Signature: Bojan Pečavar