



Ref. Certif. No.

SE-87958

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

ITE POWER SUPPLY

Name and address of the applicant

GLOBTEK INC
186 VETERANS DRIVE NORTHVALE NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100 – 240 Vac, 50 – 60 Hz, 1.0 A
Output: 12 – 48 Vdc, Max. 3.3 A
Class II

Trademark (if any)

 **GlobTek, Inc.** (GlobTek)

Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT-41083-****-*. *-T2

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 60950-1:2005+A1+A2
(EN 60950-1:2006 and A11+A1+A12+A2)

As shown in the Test Report Ref. No. which forms part
of this Certificate

170601843SHA-001


This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 14 August 2017

Intertek

Signature:


Gary Hu



Ref. Certif. No.

SE-87958**Factories**

1. GLOBTEK INC
186 VETERANS DRIVE NORTHVALE NJ 07647 USA
2. GlobTek (Suzhou) Co., Ltd.
Building 4, No. 76, JinLing East Road., Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Additional information (if necessary)

Explanation of model GT-41083-****-*. *-T2:

The first together with the second symbol "**" denote the watt, which can be 01-41, with interval of 1.

The third together with the fourth symbol "**" denote the standard rated output voltage designation, which can be "12", "24", "48".

The symbols "-*. *" denote the optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-23.9" with interval of 0.1, or blank to indicate no voltage different.

The 3rd to 6th asterisks together denote the output voltage with a range of 12-48 volts.

The model designations and ratings are detailed as follows:

MODEL	Output Voltage	Max. Output Current	Max. Output Watt
GT-41083-**12-T2	12Vdc	3.3A	40W
GT-41083-**24-*. *-T2	12.1-24Vdc	3.3A	40W
GT-41083-**48-*. *-T2	24.1-48Vdc	1.7A	41W

The group- and national differences for the CENELEC countries, and the national differences for Canada, China, Korea, Japan, USA, Australia and New Zealand have been checked.

Date: 14 August 2017

Signature: