



Ref. Certif. No.

SE-78078

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

Switching mode power supplies for general purpose

Name and address of the applicant
Nom et adresse du demandeur

GlobTek Inc
186 Veterans Drive, Northvale NJ 07647, United States

Name and address of the manufacturer
Nom et adresse du fabricant

Same as above

Name and address of the factory
Nom et adresse de l'usine
Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page

See page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

See page 2

Trademark (if any)
Marque de fabrique (si elle existe)

GlobTek

Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

-

Model / Type Ref.
Ref. De type

GT-41134-0606-W2-TAB, GT*41134-***-***

Additional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la 2^{ème} page)

See page 2

A sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à la

IEC 61558-1: 2005+A1
IEC 61558-2-16:2009+A1

As shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport d'essais numéro de référence qui constitue partie de ce Certificat

141101780SHA-001

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 17 December 2014

Intertek

Signature:

Gary Hu

**Factories
Les usines**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, United States

**Additional information (if necessary)
Information complémentaire (si nécessaire)**

GT*41134-***-***.

The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "*" denotes the rated output wattage designation, which can be "01" to "06", with interval of 1.

The 3rd "*" denotes the standard rated output voltage designation, which can be "06", "12", "15", "18", "24", "36" or "48".

The 4th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-11.9" with interval of 0.1, or blank to indicate no voltage different.

The 3rd "*" and 4th "*" together denote the output voltage, with a range of 5 - 48 volts.

The 5th "*" can be "F" or "FW" to denote open frame model with connector which is fixing on the PCB.

"F" represent models with Class I connector and "FW" represent models with Class II connector.

The 6th "*" can be blank or "T".

When the 6th "*" is "T" to denote open frame model with appliance inlet.

When the 6th "*" is "T", the 7th "*" can be "2" representing models with Class II inlet or "3" and "3A" representing model with two types of Class I inlets C14 and C6 respectively. When the 6th "*" is blank, the 7th "*" is blank too. The last three asterisks with hyphen "-***" are blank to denote direct plug-in model series.)

Model	voltage	Max. current	Max. power
GT*41134-*06*-***	5-6V	1.2A	6W
GT*41134-*12*-***	6.1-12V	0.98A	6W
GT*41134-*15*-***	12.1-15V	0.50A	6W
GT*41134-*18*-***	15.1-18V	0.40A	6W
GT*41134-*24*-***	18.1-24V	0.33A	6W
GT*41134-*36*-***	24.1-36V	0.25A	6W
GT*41134-*48*-***	36.1-48V	0.16A	6W

Date: 17 December 2014

Signature: 

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

GT-41134-0606-W2-TAB:

Class II, IP20, ta: 50°C;

Input: 120V~, 60 Hz, 0.3A; Output: 6VDC, 1A; with fixed integral plug.

GT*41134-***-***: Class II, IP20, ta: 40°C;

Class II construction for GT*41134-***-FW and GT*41134-***-FWT2;

Class I construction for GT*41134-***-F, GT*41134-***-FT3 and GT*41134-***-FT3A;

Input: 100-240V~, 50-60Hz, 0.6A;

Output: 5-48VDC, 6W max; with detachable integral plug or open frame construction.

Date: 17 December 2014

Signature: 