



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2015010907830000

Valid from: Sep.07,2023

Valid until: Dec.16,2025

**NAME AND REGISTERED
ADDRESS OF THE APPLICANT**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND REGISTERED
ADDRESS OF THE
MANUFACTURER**

GlobTek,Inc.
186 Veterans Dr. Northvale, NJ 07647 / USA

**NAME AND LOCATION
OF THE FACTORY**

GlobTek (Suzhou) Co., Ltd
Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)

ITE POWER SUPPLY
See appendix (Altitude up to 5000m)

**STANDARDS AND
TECHNICAL REQUIREMENTS**

GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Dec.17,2015

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2015010907830000

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT-46180-WWVV-X.XX***** (WW can be "01" 至 "18" , stepped 1 , Represents the rated output power ; VV can be "05"、"09"、"12"、"15"、"18"、"24" ; -X.XX can be blank or "-0.01" to "-5.9" , stepped 0.01; VV-X.XX Represents the rated output voltage , range 5-24V ; "*" can be 0-9 or A-Z or [] or blank , Represents the purpose of the market)

Input : 100-240Vac,50-60Hz,0.6A ; The output specifications are shown in the following table :

| Model | DC output voltage (Vdc) | Maximum output current (A) | Maximum output power (W) |
|-------------------------|------------------------------|---------------------------------|-------------------------------|
| GT-46180-WW05***** | 5V | 3.2A | 16 |
| GT-46180-WW09-X.XX***** | 5.01-9V | 3.2A | 18 |
| GT-46180-WW12-X.XX***** | 9.01-12V | 1.99A | 18 |
| GT-46180-WW15-X.XX***** | 12.01-15V | 1.49A | 18 |
| GT-46180-WW18-X.XX***** | 15.01-18V | 1.19A | 18 |
| GT-46180-WW24-X.XX***** | 18.01-24V | 0.99A | 18 |



CHINA QUALITY CERTIFICATION CENTRE