

CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2016010907835357 Valid from: Nov.15,2023 **Valid until:** Dec.16,2025

NAME AND REGISTERED GlobTek,Inc.

ADDRESS OF THE APPLICANT 186 Veterans Dr. Northvale, NJ 07647 / USA

NAME AND REGISTERED GlobTek,Inc.

ADDRESS OF THE 186 Veterans Dr. Northvale, NJ 07647 / USA MANUFACTURER

NAME AND LOCATION GlobTek (Suzhou) Co., Ltd

OF THE FACTORY Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China.

PRODUCT MODEL(S)ITE POWER SUPPLY

See appendix (Altitude up to 2000m) (Sale without cord set)

STANDARDS AND GB 17625.1-2022 (Class A) ;GB 4943.1-2022;GB/T 9254.1-2021

TECHNICAL REQUIREMENTS

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2023)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jan.06,2016

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



http://www.cqc.com.cn

signature: 谢肇煦



Tel: +86 10 83886666



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2016010907835357

page1 of 1

Tel: +86 10 83886666

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

GT-46200-WWVV-X.XX-TZ****** (WW can be "01" to "20", stepped 1, represent for standard output wattage; VV can be "05" or "06"; when VV is "05", -X.XX is blank; when VV is "06", X.XX can be "0.05" to "0.9", stepped 0.01; The difference VV and X.XX represents the rated output voltage of the product, range 5-5.95V; "*" can be 0-9 or A-Z or () [] or blank, for marketing purposes; Z can be "3" or "3A", Represents different input sockets)

Input: 100-240V ~, 50-60Hz, 0.5A。 Output: 5-5.95V, Max. 20W。

Model	DC Output voltage	Max Output current	Max power
GT-46200-WW05-TZ*****	5V	4.0A	20W
GT-46200-WW06-X.XX-TZ*****	5.1-5.95V	3.0A	18W

