



Ref. Certif. No.

SE-89182

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

CB TEST CERTIFICATE

Product

Power supply (Limited use for House Hold products only)

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.5A;
Output: 12-24VDC, Max. 5A, Max. 65W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*46600-*****

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 60335-1:2010+A1+A2

As shown in the Test Report Ref. No. which forms part
of this Certificate

170702157SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 1 December 2017

Intertek

Signature:


Gary Hu

Factories

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road Suzhou Industrial Park Suzhou JiangSu, 215021 China

Additional information (if necessary)

Explanation of type designation GT*46600-*****

The 1st symbol "*" part can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd symbol "*" denotes the rated output wattage designation, which can be "01" to "65", with interval of 1.

The 3rd symbol "*" denotes the standard rated output voltage designation, which can be "12", "15" or "24".

The 4th symbol "*" is optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-8.9" with interval of 0.1, or blank to indicate no voltage different.

The 3rd and 4th "*" together denote the output voltage, with a range of 12 - 24 volts.

The 5th "*" =-T2 means desktop class II with C8 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

The last * denote any one character, which can be 0-9 or B-Z or ()[] or - or blank for marketing purposes.

Model List:

Model	Input	Max. output voltage (Vdc)	Max. output current (A)	Max. output power (W)
GT*46600-*12***	100-240V~, 50-60Hz, 1.5A	12Vdc	5A	60W
GT*46600-*15***		12.1-15.0Vdc	5A	60W
GT*46600-*24***		15.1-18.9Vdc	4A	60W
GT*46600-*24***		19.0-24.0Vdc	3.42A	65W

Date: 1 December 2017

Signature:

