



Ref. Certif. No.

**SE-86584**

**IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME**

**CB TEST CERTIFICATE**

Product

Power supply (Limited use for House Hold products only)

Name and address of the applicant

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 0.6A / 1.0A / 1.5A;  
Output: 5-36VDC, Max. 4.5A, Max. 36W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT\*96180-\*\*\*\*\*, GT\*96300-\*\*\*\*\*, GT\*91120-\*\*\*\*\*,  
GTM91128LI1CEL, GTM91128LI2CEL, GTM91128LI3CEL

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010+A1

As shown in the Test Report Ref. No. which forms part of this Certificate

151100939SHA-001

This CB Test Certificate is issued by the National Certification Body

**Intertek Semko AB**  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

**Intertek**

Signature:

Hyden Li

Date: 10 April 2017



Ref. Certif. No.

SE-86584

**Factories**

1, GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

2, GlobTek ( Suzhou) Co., Ltd  
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

**Additional information (if necessary)**

Group differences for CENELEC countries are considered.

**Model similarity:**

GT\*96180-\*\*\*\*\*,

The 1st "\*" part can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd "\*" denotes the rated output wattage designation, which can be "01" to "18", with interval of 1.

The 3rd "\*" denotes the standard rated output voltage designation, which can be "07", "11", "17.9", "30" or "38";

The 4th "\*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-12.0" with interval of 0.01, or blank to indicate no voltage different.

The 3rd "\*" and 4th "\*" together denote the output voltage, with a range of 5 - 36 volts.

The 5th "\*" = blank, it means wall plug in with interchangeable blade

- =-T2 means desktop class II with C8 AC inlet
- =-T2A means desktop class II with C18 AC inlet
- =-T3 means desktop class I with C14 AC inlet
- =-T3A means desktop class I with C6 AC inlet

The last \* denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

GT\*96300-\*\*\*\*\* and GT\*91120-\*\*\*\*\*

The 1st "\*" part can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd "\*" denotes the rated output wattage designation, which can be "01" to "36", with interval of 1.

The 3rd "\*" denotes the standard rated output voltage designation, which can be "07.5", "10.5", "14.5", "19.5", "24" or "36".

The 4th "\*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-12.0" with interval of 0.01, or blank to indicate no voltage different.

The 3rd "\*" and 4th "\*" together denote the output voltage, with a range of 5 - 36 volts.

The 5th "\*" =-T2 means desktop class II with C8 AC inlet

- =-T2A means desktop class II with C18 AC inlet
- =-T3 means desktop class I with C14 AC inlet
- =-T3A means desktop class I with C6 AC inlet
- =-R2 means hybrid desktop housing class II with C8 AC inlet
- =-R3A means hybrid desktop housing class I with C6 AC inlet

The last \* denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

**Ratings**

GT\*96180-\*\*\*\*\*, Input: 100-240V~, 50-60Hz, 0.6A, Output: 5-36Vdc, Max. 3.6A, Max. 18W

GT\*96300-\*\*\*\*\*, Input: 100-240V~, 50-60Hz, 1.5A or 1.0A, Output: 5-36Vdc, Max. 4.5A, Max. 36W

GT\*91120-\*\*\*\*\*, Input: 100-240V~, 50-60Hz, 1.5A or 1.0A, Output: 5-36Vdc, Max. 4A, Max. 30W

GTM91128LI1CEL, Input: 100-240V~, 50-60Hz, 0.6A, Output: 4.2Vdc, 1.0A

GTM91128LI2CEL, Input: 100-240V~, 50-60Hz, 0.6A, Output: 8.4Vdc, 1.0A

GTM91128LI3CEL, Input: 100-240V~, 50-60Hz, 0.6A, Output: 12.6Vdc, 1.0A

Date: 10 April 2017

Signature: