



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2017010907979195

Valid from: Jun.09,2022

Valid until: May.26,2027

NAME AND REGISTERED ADDRESS OF THE APPLICANT	GlobTek,Inc. 186 Veterans Dr. Northvale, NJ 07647 / USA
NAME AND REGISTERED ADDRESS OF THE MANUFACTURER	GlobTek,Inc. 186 Veterans Dr. Northvale, NJ 07647 / USA
NAME AND LOCATION OF THE FACTORY	GlobTek (Suzhou) Co.,Ltd. Building 4, No. 76 JinLing East Road,Suzhou Industrial Park, Suzhou, JiangSu, China.
PRODUCT MODEL(S)	ITE POWER SUPPLY See appendix (Altitude up to 5000m) (Sale without cord set)
STANDARDS AND TECHNICAL REQUIREMENTS	GB 17625.1-2012;GB 4943.1-2011;GB/T 9254-2008

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C09-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Jul.03,2017

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2017010907979195

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

Model: GT*96300-**-***

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification;

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “36”, with interval of 1V.

The 3rd “*” denotes the standard rated output voltage designation, which can be “48”, “54” or “56”;

The 4th “*” can be T2 or T2A or R2, T2 and R2 mean C8 AC inlet, T2A means C18 AC inlet;

The 5th “*” can be -AP or -PP or -SP, -AP (with baby board) stands for Active POE (full IEEE compliant),

-PP (no baby board) stands for Passive POE, -SP (no baby board) stands for Simple POE;

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes;

The 1st “*” and 6th “*” do not affect product safety and EMC.

Input: 100-240Vac, 50-60Hz, 0.6A or 1.0A or 1.5A

Rating:

Models	Output Voltage (Vdc)	Max. Output Current (A)	Max. Output Power (W)
GT*96300-*48-T2/T2A/R2-AP/PP/SP*	48Vdc	0.75A	36W
GT*96300-*54-T2/T2A/R2-AP/PP/SP*	54Vdc	0.66A	36W
GT*96300-*56-T2/T2A/R2-AP/PP/SP*	56Vdc	0.64A	36W



CHINA QUALITY CERTIFICATION CENTRE