




Reference No. : WTX21X09095480E-2
 Holder : GlobTek, Inc.
 Address : 186 Veterans Dr. Northvale, NJ 07647 USA
 Product : Medical/ITE Power Supply
 Trade Name : 
 Model(s) : See Model List
 Ratings : Refer to the test report

Test Standards:

EN 60601-1-2:2015

EN 60601-1-2:2015 Medical electrical equipment – Part 1-2: General requirements for basic safety and essential performance – Collateral standard: Electromagnetic compatibility – Requirements and tests



The statement is based on a single evaluation of the sample of above mentioned product(s). It does not imply an assessment of the whole production.

Waltek Testing Group (Shenzhen) Co., Ltd.

Tel: +86-755-3366 3308

Fax: +86-755-3366 3309

Http://www.waltek.com.cn

E-mail: sem@waltek.com.cn

ANNEX 1 TO ADDING MODEL



Certificate No. : WTX21X09095480E-2

Model List

GTM96180-1811-2.0-T3, GTM91120-3024-T3A, GTM96300-3624-T2

GT*96180-*****, GT*96300-*****, GT*91120-*****,

GT*96180-*****,

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “18”, with interval of 1.

The 3rd “*” denotes the standard rated output voltage designation, which can be “07”, “11”, “17.9”, “30”, “38”, “48”, “54” or “56” ;

The 4th “*” is optional deviation, subtracted from standard output voltage, which can be “-0.01” to “-12.0” with interval of 0.01, or blank to indicate no voltage different.

The 3rd “*” and 4th “*” together denote the output voltage, with a range of 5 - 56 volts.

The 5th “*” = blank, it means wall plug in with interchangeable blade

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

The 6th “*” = Blank or -AP or -PP or -SP

-AP (with baby board) stands for Active POE (full IEEE compliant)

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

The last * denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Ratings

When the 6th “*” is blank:

GT*96180-*****, Input: 100-240V~, 50-60Hz or 50/60Hz, 0.6A, Output: 5-48Vdc, Max. 3.6A, Max. 18W

When the 6th “*” = -AP or -PP or -SP:

GT*96180-*****, Input: 100-240V~, 50-60Hz or 50/60Hz, 0.6A, Output: 18-56Vdc, Max. 1.0A, Max. 18W

GT*96300-***** and GT*91120-*****

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “36”, with interval of 1.

Waltek Testing Group (Shenzhen) Co., Ltd.

Tel: +86-755-3366 3308

Fax: +86-755-3366 3309

Http://www.waltek.com.cn

E-mail: sem@waltek.com.cn

The 3rd “*” denotes the standard rated output voltage designation, which can be “07.5” , “10.5” , “14.5” , “19.5” , “24” , “36” , “48” , “54” or “56” ;

The 4th “*” is optional deviation, subtracted from standard output voltage, which can be “-0.01” to “-11.9” with interval of 0.01, or blank to indicate no voltage different.

The 3rd “*” and 4th “*” together denote the output voltage, with a range of 5 - 56 volts.

The 5th “*” =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-R3A means hybrid desktop housing class I or class II with functional earth with C6 AC inlet

=-F means Open Frame class I or class II with functional earth

=-FW means Open Frame class II

=-P2 means Encapsulated class II

=-P3 means Encapsulated class I or class II with functional earth

The 6th “*” = Blank or -AP or -PP or -SP

-AP (with baby board) stands for Active POE (full IEEE compliant)

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

The last * denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Ratings

When the 6th “*” is blank:

GT*96300-*****, Input: 100-240V~, 50-60Hz or 50/60Hz, 1.0A, Output: 5-48Vdc, Max. 4.5A, Max. 36W

GT*91120-*****, Input: 100-240V~, 50-60Hz or 50/60Hz, 1.5A, Output: 5-48Vdc, Max. 4A, Max. 30W

When the 6th “*” = -AP or -PP or -SP:

GT*96300-*****, Input: 100-240V~, 50-60Hz or 50/60Hz, 1.0A, Output: 18-56Vdc, Max. 2.0A, Max. 36W

Waltek Testing Group (Shenzhen) Co., Ltd.

Tel: +86-755-3366 3308

Fax: +86-755-3366 3309

Http://www.waltek.com.cn

E-mail: sem@waltek.com.cn