



Proof of Compliance

Document Number PoC9677

Certificate Holder GlobTek, Inc.
186 Veterans Drive
Northvale NJ 07647
USA

Product Description ITE Power Supply (Desktop type or Direct Plug-in)
Trade Name G GLOBTEK, INC.
Model Numbers GT**_***** Series

Name Plate Ratings I/P 100-240V~ 50-60Hz 0.6A or 1.0A or 1.5A
 O/P 5-56Vdc, 1-36W, Class II

N136 Pty Ltd declares that the electrical article as described above meets the requirements of the standards listed below

Standard
AS/NZS 60950.1:2011 Inc A1
EN 55032:2012

Evidenced by
Certificate of Approval SAA-161679-EA issued 28 September 2016
N136 ACMA DoC CF9677_AU issued 9 December 2016

Compliance Mark/s

RCM; SAA-161679-EA

Initial Date of Issue
Expiry Date

9 December 2016
28 September 2021

For and on behalf of

Pty Ltd

Registered Office Unit 4R 5 Rocla Road Traralgon Vic 3844 Australia



Addendum 01 to

Document Number PoC9677

Product Description ITE Power Supply (Desktop type or Direct Plug-in)
Date Of Issue 9 December 2016

General Modification:

The 1st '*' can be 'M', '-' or 'H' and is for marketing purposes only.

The 2nd '*' denotes market identification and can be '96180', '96300', '91120' or '91128';

The 3rd '*' denotes rated output wattage designation (W) and can be '01-36' in steps of 1W;

The 4th '*' denotes standard rated output voltage designation:

when 2nd '*' = '96180', 4th '*' can be '07', '11', '17.9', '30', '38', '48', '54' or '56';

when 2nd '*' = '96300' or '91120', 4th '*' can be '07.5', '10.5', '14.5', '19.5', '24', '36', '48', '54' or '56';

The 5th '*' denotes optional deviation, subtracted from standard output voltage, which can be '-0.01' to '-12.0' in steps of 0.01, or blank to indicate no voltage different.

(Note: the 4th '*' and 5th '*' together denote the output voltage with a range of 5-56V);

The 6th '*' denotes type and can be:

blank for plug-in type with interchangeable plug;

'-T2' for desktop, class II, with C8 AC inlet,

'-T2A' for desktop, class II, with C18 AC inlet,

'-T3' for desktop, class I, with C14 AC inlet, or

'-T3A' for desktop, class I, with C6 AC inlet;

The 7th '*' denotes POE function and can be:

'-AP' (with baby board) Active POE (IEEE compliant),

'-PP' (no baby board) Passive POE or

'-SP' (no baby board) Simple POE;

(Note: When 2nd '*' = '91128', the model will be 'GTM91128LI1CEL' (Output: 4.2V, 1000mA), 'GTM91128LI2CEL'

(Output: 8.4, 1000mA) or 'GTM91128LI3CEL' (Output: 12.6V, 1000mA); and

The 8th '*' can be a combination of six characters of the following: '0-9', 'A-Z', '(', ')', '[', ']', '-', or blank and is for marketing purposes only.

For and on behalf of

i136 Pty Ltd

Registered Office 4R 5 Rocla Road Traralgon Vic 3844