



Ref. Certif. No.

SE-77824M1

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE Power Supply

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory

Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

See page 2

Trademark (if any)

GlobTek

Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*43007-*****

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part of this Certificate

140900434SHA-002, 140900434SHA-002 M1

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00



Signature:

Gary Hu

Date: 23 August 2017



Ref. Certif. No.

SE-77824M1

Factories

1. GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA

2. GlobTek (Suzhou) Co., Ltd
Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou, JiangSu 215021, China

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.5A

Model	Output Voltage	Max. output current	Max. output power	Transformer
GT*43007-**05*	5V	6A	30W	TF024 (5-6.5Vdc) TF025 (6.6-8.9Vdc) TF026 (9-13Vdc) TF027 (13.1-17Vdc) TF028 (17.1-24.9Vdc) TF029 (25-34.9Vdc) TF032 (35-48Vdc)
GT*43007-**07**	5.1-7V	6A	30W	
GT*43007-**09**	7.1-9V	5A	45W	
GT*43007-**12**	9.1-12V	5.0A	60W	
GT*43007-**15**	12.1-15V	5.0A	60W	
GT*43007-**18**	15.1-18V	4.0A	60W	
GT*43007-**24**	18.1-24V	3.31A	60W	
GT*43007-**36**	24.1-36V	2.50A	60W	
GT*43007-**48**	36.1-48V	1.66A	60W	

Additional information (if necessary)

This certificate replaces CB certificate SE-77824, dated 20 November 2014. A new certificate has been issued due to:

1. Increasing the max. output power for model GT*43007-**12** from 45W to 60W.
2. Updating national difference for Japan and Australia/New Zealand
3. Adding alternative PCB material, fuse and heatsink in critical component list.

Group differences for CENELEC countries and national difference for Singapore, Japan, China, Australia/New Zealand, Korea, Canada and USA have been checked.

Explanation of model GT*43007-****:

The 1st symbol "*" can be 'M' or 'L' or 'H' for market identification and not related to safety.

The 2nd symbol "*" is A, B, or C and is related to PCB size: A= 2"x3", B=2"x4", C=3"x5". The different PCB sizes are only for installation purpose in end product with no safety spacing modification.

The 3rd symbol "*" denotes the rated output wattage designation, which can be "01" to "60", with interval of 1.

The 4th symbol "*" denotes the standard rated output voltage designation, which can be "05", "07", "09", "12", "15", "18", "24", "36" or "48". Each standard rated output voltage designation corresponds to a transformer model. Each transformer model is identical in insulation construction including clearance and creepage except number of turns per coil.

The 5th symbol "*" is optional deviation, subtracted from standard output voltage, which can be "-0.1" to "-11.9" with interval of 0.1, or blank to indicate no voltage different.

The 4th and 5th asterisks together denote the output voltage with a range of 5-48 volts.

The 6th symbol "*" can be "-F" or "-FW". "-F" represents Class I model and "-FW" represents Class II model.

Date: 23 August 2017

Signature: