



Ref. Certif. No.

SE-95157

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

I.T.E. POWER SUPPLY

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Input: 100-240 V~, 50-60 Hz, 0.45 A;
Output: 5-5.5 Vdc, Max. 3.2 A, Max 16 W
Class II

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

--

Model / Type Ref.

GT*46161-**-*

Additional information (if necessary may also be
reported on page 2)

See page 2

A sample of the product was tested and found
to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part
of this Certificate

190700260TWN-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Date: 20 August 2019

intertek

Signature:

Ike Wang

Factories

1. GlobTek (Suzhou) Co., Ltd.
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China
2. GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647, USA

Additional information (if necessary)

The national differences for US and AU have been checked.
The product has also been checked according to EN 62368-1:2014+A11.

Explanation for model GT*46161-**-*

The 1st symbol "*" denotes "M" or "-" or "H" for market identification and not related to safety.

The 2nd symbol "*" denotes the rated output wattage designation, which can be "01" to "16", with interval of 1.

The 3rd symbol "*" denotes the standard rated output voltage designation, which can be "5.0" to "5.5" or "05" to "05.5" with interval of 0.1 Vdc.

The last symbol "*" denotes -USB means Type 1 USB*1, -USB1A means Type 2 USB*1, -USB2A means Type 2 USB*2 and -USBC means Type 2 USB Type C.

Model	Input	Output Voltage	Max. output current	Max. output power
GT*46161-*5.0-*, GT*46161-*05-*	100-240 V~, 50-60 Hz, 0.45 A	5 Vdc	3.2 A	16 W
GT*46161-**-*		5.1-5.5 Vdc	3.14 A	16 W

All models are similar except for output type and different output voltage.

Date: 20 August 2019

Signature:

