

http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

TEST REPORT

Client..... : GlobTek, Inc.

Address.....: 186 Veterans Dr. Northvale, NJ 07647 USA

Brand Name...... GlobTek, Inc.

Manufacturer.....: 1. GlobTek, Inc.

Address...... : 186 Veterans Dr. Northvale, NJ 07647 USA

2. GlobTek (Suzhou) Co., Ltd.

Building 4, No. 76, Jin Ling East Rd., Suzhou Industrial Park, Suzhou

JiangSu 215021, China

Testing Laboratory ...: Shenzhen Southern LCS Compliance Testing Laboratory Ltd.

Address..... B Area, 1-2F, Building B, Zhongyu Green High-tech Industrial

Park, Wenge Road, Heshuikou, Gongming Street, Guangming

New District, Shenzhen, China

Product Description.. : ITE / Medical Power Supply

Models.....: GT*91099-***-T**

Rating.....: 100-240V~, 50-60Hz, 60W

Method.....: IEC 60529:1989+A1:1999+A2:2013

Test Item..... : IP42

Date of Test..... : 2018-08-09~2018-08-14

Date of Issue..... 2018-08-13

Lance Ma Mrs

Test Result..... : Pass

Test by:

Check by:

Lance Mo/ Project Engineer

Eko Yang/ Director

Jesse Liu/ Manager

Version: V1.0

Page 1 of 7



http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

Remark: The duplication of this report or parts of it and its use for advertising purposes is only allowed with permission of the testing laboratory. This report contains the result of examination of the product sample submitted by the appliance. A general statement concerning the quality of the products from the series manufacturer cannot be derived therefore.

General product information:

- Unless otherwise specified, the model GTM91099-6015-3.0-T2 was chosen as representative model to perform all test.

Series description:

- GT*91099-***-T**:
- The 1st "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.
- -The 2nd" *" denotes the rated output wattage designation, which can be "01" to "60", with interval of 1;
- The 3rd "*" denotes the standard rated output voltage designation, which can be "09", "15" "24", "48";
- The 4th "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-23.9" with interval of 0.01, or blank to indicate no voltage different;
- The 3rd "*" and 4th "*" together denote the output voltage, with a range of 5 48volts;
- The 5th" *" can be 2, 2A or 3, 2 & 2A means Class II equipment, 3 means Class I;
- The last * denote any six character = 0-9 or A-Z or ()[] or or blank for marketing purposes.

Version: V1.0 Page 2 of 7



http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

Equipment used during test:

ID Number	Instrument	Model/	Calibration Date	
		Туре		
SLCS-S-095	Test needle	AGPCD	2018-08-10	
SLCS-S-032	Dripping rain test device	DJ-B	2018-01-11	
SLCS-S-135	Digital hygrometer thermometer	HTC-1	2017-10-09	

Version: V1.0 Page 3 of 7



http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

Test Item:

Acceptance conditions for first characteristic numerals 4

Atmospheric conditions for water or dust tests:

Air pressure: 86 kPa to 106 kPa Temperature range: 20℃ to 30℃ Relative humidity: 25 %RH to 75 %RH


Test samples:

Clean and new sample were be tested

Test Mothod:

The protection is satisfactory if the full diameter of the probe specified in table 6 does not pass through any opening.

Table 6 – Access probes for the tests for protection of persons against access to hazardous parts



Acceptance Conditions:

Not pass through any opening

Test Result:

Teall		
	To:] Eo:I

Version: V1.0 Page 4 of 7



http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

Test Item:

Acceptance conditions of the second characteristic number 2

Atmospheric conditions for water or dust tests:

Air pressure: 86 kPa to 106 kPa
Temperature range: 20℃ to 30℃
Relative humidity: 25 %RH to 75 %RH

Test samples:

Clean and new sample were be tested

Test Mothod:

- a. Put the sample on the table, the sample is fixed in its normal position of use;
- b. The drop box is up on the sample, the distance is 200mm;
- c. Water flow rate is 3mm/minutes;
- d. These positions are 15° on either side of the vertical in two mutually perpendicular planes.
- e. The enclosure is tested for 2,5 min in each of four fixed positions of tilt. The total duration of the is 10 min

After test, the enclosure shall be inspected for ingress of water.

Test Result:

⊠ Pass	☐ Fail			

Version: V1.0 Page 5 of 7

http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

Photo Documentation:

Photo 1: Overall view of model GTM91099-6015-3.0-T2



Photo 2: IP4X test of model GTM91099-6015-3.0-T2



Version: V1.0 Page 6 of 7

http://www.lcs-cert.com; Phone: +(86) 0755-29871520; Fax: +(86) 0755-29871521

Report No.: LCS180718034BS

Photo Documentation:

Photo 3: IPX2 test of model GTM91099-6015-3.0-T2



---- End of Test Report----

Version: V1.0 Page 7 of 7