

Certificate



Intertek


for European Product Safety

Reference No. 1708042

Medical Power supply

Type designation	GT*91099-***-**, GT*96600-***-**
Certificate holder	GLOBTEK INC 186 Veterans Drive, Northvale NJ 07647 USA
The product complies with the standard(s)	EN 60601-1:2006+A1+A12 EN 60601-1-11:2015
Date of expiry	1 March 2022

Additional information in Appendix.

Certification Body	Intertek Semko AB, Product Certification	Place	Kista - Stockholm
Signed	 Bo Berglöv	Date	1 March 2017

Page 1 of 3



Intertek Appendix

Reference No. 1708042

Technical data

Type designation	GT*91099-***-**, GT*96600-***-**
Input	1.5A, 100-240V~, 50-60Hz
Output	5-54VDC, Max 60W
Brand name:	GlobTek

Product information

Explanation of type designation GT*91099-***-** and GT*96600-***-**:

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “60”, with interval of 1.

When model= GT*91099-***-**,

The 3rd “*” denotes the standard rated output voltage designation, which can be “09”, “15”, “24”, “48”;

The 4th “*” is optional deviation, subtracted from standard output voltage, which can be “-0.01” to “-23.9” with interval of 0.01, or blank to indicate no voltage different.

The 3rd “*” and 4th “*” together denote the output voltage, with a range of 5–48volts.

When model=GT*96600-***-**,

The 3rd “*” denote the standard rated output voltage designation, which can be “05” to “54” or “5.0” to “54.0” in 0.1V increments.

The 4th “*”=Blank

The 5th “*” =T2 means desktop class II with C8 AC inlet

=T2A means desktop class II with C18 AC inlet

=T3 means desktop class I with C14 AC inlet

=T3A means desktop class I with C6 AC inlet

=T2L means desktop class II with C8 AC inlet and housing with a DC jack

=T2AL means desktop class II with C18 AC inlet and housing with a DC jack

=T3L means desktop class I with C14 AC inlet and housing with a DC jack

=T3AL means desktop class I with C6 AC inlet and housing with a DC jack

=R2 means hybrid desktop housing class II with C8 AC inlet

=R3A means hybrid desktop housing class I with C6 AC inlet

=F means Open Frame class I

=FW means Open Frame class II

=P2 means Encapsulated class II

=P3 means Encapsulated class I

The last * denote any six character = 0-9 or A-Z or ()[] or – or blank for marketing purposes.

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.



Intertek Appendix

Reference No. 1708042

For details please refer to model list table.

Alternate Rating:

For models GTM96600-2005-R2 / GTM96600-2005-R3A: output 5VDC, 4.0A at Tma=70 Deg.C;
For models GTM96600-2412-R2 / GTM96600-2412-R3A: output 12VDC, 2.0A at Tma=70 Deg.C;
For models GTM96600-2436-R2 / GTM96600-2436-R3A: output 36VDC, 0.66A at Tma=70 Deg.C;
For models GTM96600-2448-R2 / GTM96600-2448-R3A: output 48VDC, 0.5A at Tma=70 Deg.C;
For models GTM96600-2454-R2 / GTM96600-2454-R3A: output 54VDC, 0.44A at Tma=70 Deg.C;

Ratings

When model is GT*91099-***-**, Input: 100-240V~,50-60Hz, 1.5A Output: 5-48Vdc

When model is GT*96600-***-**, Input: 100-240V~,50-60Hz, 1.5A Output: 5-54Vdc

Manufacturing site(s)

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road
Suzhou Industrial Park, Suzhou JiangSu, 215021
CHINA

Safety related parts of the user instructions shall be written in a language acceptable to the country where the product is to be used.

If the product is to be marketed in different European countries, it must be provided with a certified plug appropriate for each country.

Certification Body

Intertek Semko AB, Product Certification

Place Kista - Stockholm

Signed


Bo Berglöf

Date 1 March 2017

This Certificate is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this certificate. Only the Client is authorized to permit copying or distribution of this certificate and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.