



Ref. Certif. No.

SE-83970

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST
CERTIFICATES FOR ELECTRICAL EQUIPMENT
(IECEE) CB SCHEME

SYSTEME CEI D'ACCEPTATION MUTUELLE DE
CERTIFICATS D'ESSAIS DES EQUIPEMENTS
ELECTRIQUES (IECEE) METHODE OC

CB TEST CERTIFICATE

CERTIFICAT D'ESSAI OC

Product
Produit

ITE Power Supply

Name and address of the applicant
Nom et adresse du demandeur

GlobTek, Inc.
186 Veterans Drive, Northvale, NJ 07647, USA

Name and address of the manufacturer
Nom et adresse du fabricant

Same as applicant


Name and address of the factory
Nom et adresse de l'usine
Note: When more than one factory, please report on page 2
Note: Lorsque il y plus d'une usine, veuillez utiliser la 2^{ème} page

See page 2

Ratings and principal characteristics
Valeurs nominales et caractéristiques principales

See page 2

Trademark (if any)
Marque de fabrique (si elle existe)



Type of Manufacturer's Testing Laboratories used
Type de programme du laboratoire d'essais constructeur

-

Model / Type Ref.
Ref. De type

GT**-*****:

Additional information (if necessary may also be reported on page 2)
Les informations complémentaires (si nécessaire, peuvent être indiqués sur la 2^{ème} page)

See page 2

A sample of the product was tested and found to be in conformity with
Un échantillon de ce produit a été essayé et a été considéré conforme à la

IEC 60950-1:2005+A1+A2

As shown in the Test Report Ref. No. which forms part of this Certificate
Comme indiqué dans le Rapport d'essais numéro de référence qui constitue partie de ce Certificat

151100936SHA-001

This CB Test Certificate is issued by the National Certification Body
Ce Certificat d'essai OC est établi par l'Organisme **National de Certification**

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

Intertek

Signature:

Gary Hu

Date: 27 July 2016

Factories**Les usines**

GlobTek, Inc.
186 Veterans Drive, Northvale, NJ 07647, USA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Ratings and principal characteristics**Valeurs nominales et caractéristiques principales**

When 2nd^{**} = 96180, Input: 100-240V~, 50-60Hz, 0.6A; Output: 5-56Vdc

When 2nd^{**} = 96300 or 91120, Input: 100-240V~, 50-60Hz, 1.5A or 1.0A; Output: 5-56Vdc

When the model with POE, the output voltage is Max. 56Vdc, others will be up to 48Vdc.

Additional information (if necessary)**Information complémentaire (si nécessaire)**

Explanation for model designation GT^{**}-*****:

The 1st ^{**} part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd ^{**} can be 96180 or 96300 or 91120 or 91128 for market identification

The 3rd ^{**} denotes the rated output wattage designation, which can be "01" to "36", with interval of 1.

The 4th ^{**} denotes the standard rated output voltage designation, when the 2nd^{**} = 96180 which can be "07", "11", "17.9", "30", "38", "48", "54" or "56"; when the 2nd^{**}=96300 or 91120 which can be "07.5", "10.5", "14.5", "19.5", "24", "36", "48", "54" or "56".

The 5th ^{**} is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-12.0" with interval of 0.01, or blank to indicate no voltage different.

The 4th ^{**} and 5th ^{**} together denote the output voltage, with a range of 5 - 56 volts.

The 6th ^{**} = blank, it means wall plug in with interchangeable blade

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-R3A means hybrid desktop housing class I with C6 AC inlet

=-F means Open Frame class I

=-FW means Open Frame class II

=-P2 means Encapsulated class II

=-P3 means Encapsulated class I

The 7th ^{**} = Blank or -AP or -PP or -SP

-AP (with baby board) stands for Active POE (full IEEE compliant)

-PP (no baby board) stands for Passive POE

-SP (no baby board) stands for Simple POE

When the 2nd^{**}=91128,

the model will be GTM91128LI1CEL Output: 4.2V, 1000mA;

or Model GTM91128LI2CEL Output: 8.4V, 1000mA;

or Model GTM91128LI3CEL Output: 12.6V, 1000mA;

The last * denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Group differences for CENELEC and national differences for Singapore, Japan, China, Australia/New Zealand, Korea, USA and Canada are considered.

Date: 27 July 2016

Signature: 