



Ref. Certif. No.

SE-93035

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

Power supply

Name and address of the applicant

GLOBTEK INC
186 VETERANS DRIVE, NORTHVALE NJ 07647,
USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Note: When more than one factory, please report on page 2

See page 2

Ratings and principal characteristics

Class II, IP20, ta: 40°C
Input: 100-240VAC, 50-60Hz, 0.6A
Output: 5-48VDC, Max. 3.6A, Max. 18W.

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*96180-*****

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 61558-1:2005+A1
IEC 61558-2-16:2009+A1

As shown in the Test Report Ref. No. which forms part of this Certificate

181101640SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Box 1103
SE-164 22 Kista, Sweden
Int +46 8 750 00 00

intertek

Signature:

Hyden Li

Date: 15 January 2019

Factories

1. GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647 USA
2. GlobTek (Suzhou) Co., Ltd.
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

Additional information (if necessary)

Explanation of model GT*96180-*****.

The 1st symbol "*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd symbol "*" denotes the rated output wattage designation, which can be "01" to "18", with interval of 1W.

The 3rd symbol "*" denotes the standard rated output voltage designation, which can be "07", "11", "17.9", "30", "38" or "48";

The 4th symbol "*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-12.0" with interval of 0.01, or blank to indicate no voltage different.

The 3rd "*" and 4th symbol "*" together denote the output voltage, with a range of 5 - 48 volts.

The 5th symbol "*" = blank, it means wall plug in with interchangeable blade

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

The last symbol "*" denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Group and national differences for CENELEC countries have been checked.

Date: 15 January 2019

Signature:

