




Ref. Certif. No.

SE-95488

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product	Power supply
Name and address of the applicant	GLOBTEK INC 186 Veterans Dr. Northvale, NJ 07647 USA
Name and address of the manufacturer	Same as applicant
Name and address of the factory <i>Note: When more than one factory, please report on page 2</i>	See page 2
Ratings and principal characteristics	Class II, IP20, ta: 40°C Input: 100-240VAC, 50-60Hz, 1.5A Output: 5-54 VDC, Max. 8.00A, Max. 65W.
Trademark (if any)	
Customer's Testing Facility (CTF) Stage used	-
Model / Type Ref.	GT*96600-*****, GT*91099-*****
Additional information (if necessary may also be reported on page 2)	See page 2
A sample of the product was tested and found to be in conformity with	IEC 61558-1:2005+A1 IEC 61558-2-16:2009+A1
As shown in the Test Report Ref. No. which forms part of this Certificate	180702575SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

Date: 16 September 2019

intertek

Signature:

Hyden Li

### Factories

1. GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

2. GlobTek (Suzhou) Co., Ltd.  
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

### Additional information (if necessary)

Group differences for CENELEC countries are considered.

Explanation of models GT\*96600-\*\*\*\*\*, GT\*91099-\*\*\*\*\*:

The 1st symbol "\*" can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd symbol "\*\*" denotes the rated output wattage designation, which can be "01" to "65", with interval of 1.

For GT\*96600-\*\*\*\*\*:

The 3rd symbol "\*" denotes the standard rated output voltage designation, which can be "05" to "54" or "5.0" to "54.0" in 0.1V increments.

The 4th symbol "\*" = Blank.

For GT\*91099-\*\*\*\*\*:

The 3rd symbol "\*" denotes the standard rated output voltage designation, which can be "09", "15", "24", "48";

The 4th symbol "\*" is optional deviation, subtracted from standard output voltage, which can be "-0.01" to "-23.9" with interval of 0.01, or blank to indicate no voltage different.

The 3rd symbol "\*" and 4th symbol "\*" together denote the output voltage, with a range of 5 - 48volts

The 5th symbol "\*\*"

=-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T2L means desktop class II with C8 AC inlet and housing with a DC jack

=-T2AL means desktop class II with C18 AC inlet and housing with a DC jack

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-P2 means Encapsulated class II

The last symbol "\*" denote any six character = 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Date: 16 September 2019

Signature:

