

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR  
ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product

Power supply (Limited use for House Hold products only)

Name and address of the applicant

GlobTek, Inc  
186 Veterans Dr. Northvale, NJ 07647  
USA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


See page 2

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

Input: 100-240V~, 50-60Hz, 1.5A;  
Output: 5-36VDC, Max. 60W

Trademark (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT\*96600-\*\*\*\*\*, GT\*91099-\*\*\*\*\*

Additional information (if necessary may also be reported on page 2)

See page 2

A sample of the product was tested and found to be in conformity with

IEC 60335-1:2010+A1

As shown in the Test Report Ref. No. which forms part of this Certificate

160900317SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB  
Box 1103  
SE-164 22 Kista, Sweden  
Int +46 8 750 00 00

Date: 24 March 2017

Intertek

Signature:

Gary Hu

**Factories**

GlobTek, Inc.  
186 Veterans Dr. Northvale, NJ 07647 USA

GlobTek (Suzhou) Co., Ltd  
Building 4, No. 76 JinLing East Road, Suzhou Industrial Park, Suzhou, JiangSu, 215021, China

**Additional information (if necessary)**

Explanation of type designation GT\*96600-\*\*\*\*\*, GT\*91099-\*\*\*\*\*:

The 1st "\*" part can be 'M' or '-' or 'H' for market identification and not related to safety.

The 2nd "\*" denotes the rated output wattage designation, which can be "01" to "60", with interval of 1.

The 3rd "\*" denotes the standard rated output voltage designation, for GT\*91099-\*\*\*\*\*, which can be "09", "15", "24", "48"; for GT\*96600-\*\*\*\*\*, which can be "05" to "36" or "5,0" to "36,0" in 0.1V increments.

The 4th "\*" is optional deviation, subtracted from standard output voltage, for GT\*91099-\*\*\*\*\*, which can be "-0,01" to "-23,9" with interval of 0,01, or blank to indicate no voltage different; for GT\*96600-\*\*\*\*\*, the 4th "\*" is blank indicated no voltage different.

The 3rd "\*" and 4th "\*" together denote the output voltage, with a range of 5-36volts.

The 5th "\*" =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I with C14 AC inlet

=-T3A means desktop class I with C6 AC inlet

=-T2L means desktop class II with C8 AC inlet and housing with a DC jack

=-T2AL means desktop class II with C18 AC inlet and housing with a DC jack

=-T3L means desktop class I with C14 AC inlet and housing with a DC jack

=-T3AL means desktop class I with C6 AC inlet and housing with a DC jack

=-R2 means hybrid desktop housing class II with C8 AC inlet

=-R3A means hybrid desktop housing class I with C6 AC inlet

The last \* denote any six character = 0-9 or A-Z or () or - or blank for marketing purposes.

Date: 24 March 2017

Signature: 