

## Ref. Certif. No.

SE-101438

# IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## CB TEST CERTIFICATE

Product	Building-in Power Supply			
Name and address of the applicant	GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647, USA			
Name and address of the manufacturer	Same as applicant			
Name and address of the factory Note: When more than one factory, please report on page 2	See page 2			
Ratings and principal characteristics	Input: 100-240V~ or 100-277V~, 50-60Hz, 2.0A Output: 5-56 VDC, Max. 8.00A, Max. 70W.			
Trademark (if any)	GiobTek, Inc.			
Customer's Testing Facility (CTF) Stage used	-			
Model / Type Ref.	GT*96700-****			
Additional information (if necessary may also be reported on page 2)	See page 2			
A sample of the product was tested and found to be in conformity with	IEC 62368-1:2014			
As shown in the Test Report Ref. No. which forms part of this Certificate	200300442SHA-001			
This CB Test Certificate is issued by the National Certification Body				
Intertek Semko AB Torshamnsgatan 43 Box 1103	intertek			
SE-164 22 Kista, Sweden	1			
Date: 16 June, 2020	Signature: Gary Hu			

Ref. Certif. No.



### SE-101438

#### Factories

GlobTek, Inc. 186 Veterans Dr. Northvale, NJ 07647, USA

GlobTek (Suzhou) Co., Ltd. Building 4, No.76, JinLing East Road, Suzhou Industrial Park, Suzhou, 215021 Jiangsu, China

#### Additional information (if necessary)

Group differences for CENELEC and national differences for USA and Canada, Japan, Australia and New Zealand are considered.

Explanation of the symbol "\*" in type designation GT\*96700-\*\*\*\*\*.

The symbol can be:

The 1st "\*" part can be 'M' or '-' or 'H' for market identification and not related to safety. The 2nd "\*" can be B or C and is related to PCB size: B=2"x4", C=3"x5". The 3rd "\*" denotes the rated output wattage designation, which can be "01" to "70", with interval of 1W. The 4th "\*" denote the standard rated output voltage designation, which can be "05" to "56" or "5.0" to "56.0" in 0.1V increments.

The 5th "\*" can be -F or -FW, -F means Class I, -FW means Class II.

The last \* denote any six character, which can be 0-9 or A-Z or ()[] or - or blank for marketing purposes.

Model List:

Model	Input	Output Voltage	Max. output current	Max. output power
GT*96700-***** 100-240V~ or 100-277 50-60Hz, 2.0A		5-8.9Vdc	8.00A	49W
	100-240V∼ or 100-277V∼, 50-60Hz, 2.0A	9-44Vdc	5.42A	65W
		44.1-56Vdc	1.48A	70W

Signature: HU