



Ref. Certif. No.

SE-113583

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

CB TEST CERTIFICATE

Product

ITE/ ICT POWER SUPPLY

Name and address of the applicant

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647
UNITED STATES OF AMERICA

Name and address of the manufacturer

Same as applicant

Name and address of the factory


Additional Information on page 2

Note: When more than one factory, please report on page 2

Ratings and principal characteristics

See page 2

Trademark / Brand (if any)



Customer's Testing Facility (CTF) Stage used

-

Model / Type Ref.

GT*961200P****, GT*96900P****, GT*41133-*****

Additional information (if necessary may also be reported on page 2)

Additional Information on page 2-3

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2018

As shown in the Test Report Ref. No. which forms part of this Certificate

240100039SHA-001

This CB Test Certificate is issued by the National Certification Body

Intertek Semko AB
Torshamnsgatan 43
Box 1103
SE-164 22 Kista, Sweden

Date: 18 March, 2024

Signature:

Hyden Li



Ref. Certif. No.

SE-113583

Factories

GlobTek, Inc.
186 Veterans Dr. Northvale, NJ 07647
UNITED STATES OF AMERICA

GlobTek (Suzhou) Co., Ltd.
Building 4, No.76, JinLing East Road
Suzhou Industrial Park, Suzhou, 215021 Jiangsu
CHINA

Ratings and principal characteristics

When model = GT*41133-****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-48Vdc, Max. 7.5A, Max. 90W.
When model = GT*96900P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 7.5A, Max. 90W.
When model = GT*961200P****, Input: 100-240V~, 50-60Hz, 1.5A; Output: 12-54Vdc, Max. 9.2A, Max. 120W.

Additional information

Group differences for CENELEC and national differences for USA and Canada, Japan, Australia and New Zealand are considered.

Date: 18 March, 2024

Signature:

Additional information

Model similarity:

GT*961200P****, GT*96900P**** and GT*41133-*****

The 1st “*” part can be ‘M’ or ‘-’ or ‘H’ for market identification and not related to safety.

When model = GT*41133-*****

The 2nd “*” denotes the rated output wattage designation, which can be “01” to “90”, with interval of 1.

The 3rd “*” denotes the standard rated output voltage designation, which can be “16”, “24”, “35” and “48”.

The 4th “*” part is optional, which can be “-0.1” to “-12.9” with interval of 0.1 to denote voltage deviation or blank to indicate no voltage different.

The 3rd “*” and 4th “*” together denote the output voltage, with a range of 12 - 48 volts

The 5th “*” =-T2 means desktop class II with C8 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

=-F means Open Frame class I or class II with functional earth

=-FW means Open Frame class II

The last * denote any six character = 0-9 or A-Z or () [] or – or blank for marketing purposes.

When model = GT*961200P**** and GT*96900P****

The 2nd “*” denotes the rated output wattage designation, which can be “-01” to “-120”, with interval of 1 and “-” can be omitted.

The 3rd “*” denote the standard rated output voltage designation, which can be “12” to “54” or “12.0” to “54.0” in 0.1V increments

The 4th “*” =-T2 means desktop class II with C8 AC inlet

=-T2A means desktop class II with C18 AC inlet

=-T3 means desktop class I or class II with functional earth with C14 AC inlet

=-T3A means desktop class I or class II with functional earth with C6 AC inlet

=-T3TAB means desktop class I or class II with functional earth with C14 AC inlet and housing with a tab.

=-TW means desktop class II with input wire without plug

=-TW3 means desktop class I or class II with functional earth with input wire without plug

=-TP means desktop class II with power supply cord with plug

=-TP3 means desktop class I or class II with functional earth with power supply cord with plug

=-P2 means Encapsulated Type, class II, with two-core input wire, IP68

=-P3 means Encapsulated Type, class I or class II with functional earth, with three-core input wire, IP68

The last * denote any six character = 0-9 or A-Z or () [] or – or blank for marketing purposes

Date: 18 March, 2024

Signature:

